

~~G01N 21/64~~~~G01N 33/533~~~~G01N 33/580~~AL PROPERTY ORGANIZATION
national Bureau

UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification: <u>G01N 33/58, 21/64</u>	AI	(11) International Publication Number: WO 94/07142 (43) International Publication Date: 31 March 1994 (31.03.94)
(21) International Application Number: PCT/US93/08712 (22) International Filing Date: 14 September 1993 (14.09.93) (30) Priority data: 07/946,068 14 September 1992 (14.09.92) US (71) Applicant: SRI INTERNATIONAL [US/US]; 333 Ravenswood Avenue, Menlo Park, CA 94025 (US). (72) Inventors: ZARLING, David, A. ; 32 Lorelei Lane, Menlo Park, CA 94025 (US). ROSSI, Michel, J. ; 2, la Graveyre, CH-1312 Eclépens (CH). PEPPERS, Norman, A. ; 3619 Hillcrest Drive, Belmont, CA 94002 (US). KANE, James ; 32 Royal Oak Road, Lawrenceville, NJ 08648 (US). FARIS, Gregory, W. ; 1259 Hoover Street, Menlo Park, CA 94025 (US). DYER, Mark, J. ; 705 Blackfoot Court, San Jose, CA 95123 (US).	(74) Agents: DUNN, Tracy, J. et al. : Townsend and Townsend Kourie and Crew, One Market Plaza, 20th Fl., Steuart Street Tower, San Francisco, CA 94105 (US). (81) Designated States: CA, JP, KR, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>	
(54) Title: UP-CONVERTING REPORTERS FOR BIOLOGICAL AND OTHER ASSAYS USING LASER EXCITATION TECHNIQUES (57) Abstract The invention provides methods, compositions, and apparatus for performing sensitive detection of analytes, such as biological macromolecules and other analytes, by labeling a probe molecule with an up-converting label. The up-converting label absorbs radiation from an illumination source and emits radiation at one or more higher frequencies, providing enhanced signal-to-noise ratio and the essential elimination of background sample autofluorescence. The methods, compositions, and apparatus are suitable for the sensitive detection of multiple analytes and for various clinical and environmental sampling techniques.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NE	Niger
BE	Belgium	GN	Guinea	NL	Netherlands
BF	Burkina Faso	GR	Greece	NO	Norway
BG	Bulgaria	HU	Hungary	NZ	New Zealand
BJ	Benin	IE	Ireland	PL	Poland
BR	Brazil	IT	Italy	PT	Portugal
BY	Belarus	JP	Japan	RO	Romania
CA	Canada	KP	Democratic People's Republic of Korea	RU	Russian Federation
CF	Central African Republic	KR	Republic of Korea	SD	Sudan
CG	Congo	KZ	Kazakhstan	SE	Sweden
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovak Republic
CM	Cameroon	LU	Luxembourg	SN	Senegal
CN	China	LV	Latvia	TD	Chad
CS	Czechoslovakia	MC	Monaco	TC	Togo
CZ	Czech Republic	MG	Madagascar	UA	Ukraine
DE	Germany	ML	Mali	US	United States of America
DK	Denmark	MN	Mongolia	UZ	Uzbekistan
ES	Spain			VN	Viet Nam
FI	Finland				

5
UP-CONVERTING REPORTERS FOR BIOLOGICAL AND OTHER
ASSAYS USING LASER EXCITATION TECHNIQUES

BACKGROUND OF THE INVENTION

10 The invention relates generally to detectable labels
and compositions useful in assay methods for detecting
soluble, suspended, or particulate substances or analytes such
as proteins, carbohydrates, nucleic acids, bacteria, viruses,
and eukaryotic cells and more specifically relates to
15 compositions and methods that include luminescent
(phosphorescent or fluorescent) labels.

 Methods for detecting specific macromolecular
species, such as proteins, drugs, and polynucleotides, have
proven to be very valuable analytical techniques in biology
20 and medicine, particularly for characterizing the molecular
composition of normal and abnormal tissue samples and genetic
material. Many different types of such detection methods are
widely used in biomedical research and clinical laboratory
medicine. Examples of such detection methods include:
25 immunoassays, immunochemical staining for microscopy,
fluorescence-activated cell sorting (FACS), nucleic acid
hybridization, water sampling, air sampling, and others.

 Typically, a detection method employs at least one
analytical reagent that binds to a specific target
30 macromolecular species and produces a detectable signal.
These analytical reagents typically have two components: (1) a
probe macromolecule, for example, an antibody or
oligonucleotide, that can bind a target macromolecule with a
high degree of specificity and affinity, and (2) a detectable
35 label, such as a radioisotope or covalently-linked fluorescent
dye molecule. In general, the binding properties of the probe
macromolecule define the specificity of the detection method,
and the detectability of the associated label determines the
sensitivity of the detection method. The sensitivity of
40 detection is in turn related to both the type of label

employed and the quality and type of equipment available to detect it.

For example, radioimmunoassays (RIA) have been among the most sensitive and specific analytical methods used for

5 detecting and quantitating biological macromolecules.

Radioimmunoassay techniques have been used to detect and measure minute quantities of specific analytes, such as polypeptides, drugs, steroid hormones, polynucleotides, metabolites, and tumor markers, in biological samples.

10 Radioimmunoassay methods employ immunoglobulins labeled with one or more radioisotopes as the analytical reagent.

Radiation (α , β , or γ) produced by decay of the attached radioisotope label serves as the signal which can be detected and quantitated by various radiometric methods.

15 Radioisotopic labels possess several advantages, such as: very high sensitivity of detection, very low background signal, and accurate measurement with precision radiometric instruments (scintillation and gamma counters) or with inexpensive and sensitive autoradiographic techniques.

20 However, radioisotopic labels also have several disadvantages, such as: potential health hazards, difficulty in disposal, special licensing requirements, and instability (radioactive decay and radiolysis). Further, the fact that radioisotopic labels typically do not produce a strong (i.e., non-Cerenkov)

25 signal in the ultraviolet, infrared, or visible portions of the electromagnetic spectrum makes radioisotopes generally unsuitable as labels for applications, such as microscopy, image spectroscopy, and flow cytometry, that employ optical methods for detection.

30 For these and other reasons, the fields of clinical chemistry, water and air monitoring, and biomedical research have sought alternative detectable labels that do not require radioisotopes. Examples of such non-radioactive labels include: (1) enzymes that catalyze conversion of a chromogenic

35 substrate to an insoluble, colored product (e.g., alkaline phosphatase, β -galactosidase, horseradish peroxidase) or catalyze a reaction that yields a fluorescent or luminescent

product (e.g., luciferase) (Beck and Koster (1990) Anal. Chem. 62: 2258; Durrant, I. (1990) Nature 346: 297; Analytical Applications of Bioluminescence and Chemiluminescence (1984) Kricka et al. (Eds.) Academic Press, London), and (2) direct
5 fluorescent labels (e.g., fluorescein isothiocyanate, rhodamine, Cascade blue), which absorb electromagnetic energy in a particular absorption wavelength spectrum and subsequently emit visible light at one or more longer (i.e., less energetic) wavelengths.

10 Using enzymes and phosphorescent/fluorescent or colorimetric detectable labels offers the significant advantage of signal amplification, since a single enzyme molecule typically has a persistent capacity to catalyze the transformation of a chromogenic substrate into detectable
15 product. With appropriate reaction conditions and incubation time, a single enzyme molecule can produce a large amount of product, and hence yield considerable signal amplification. However, detection methods that employ enzymes as labels disadvantageously require additional procedures and reagents
20 in order to provide a proper concentration of substrate under conditions suitable for the production and detection of the colored product. Further, detection methods that rely on enzyme labels typically require prolonged time intervals for generating detectable quantities of product, and also generate
25 an insoluble product that is not attached to the probe molecule.

 An additional disadvantage of enzyme labels is the difficulty of detecting multiple target species with enzyme-labeled probes. It is problematic to optimize reaction
30 conditions and development time(s) for two or more discrete enzyme label species and, moreover, there is often considerable spectral overlap in the chromophore endproducts which makes discrimination of the reaction products difficult.

 Fluorescent labels do not offer the signal
35 amplification advantage of enzyme labels, nonetheless, fluorescent labels possess significant advantages which have resulted in their widespread adoption in immunocytochemistry.

Fluorescent labels typically are small organic dye molecules, such as fluorescein, Texas Red, or rhodamine, which can be readily conjugated to probe molecules, such as immunoglobulins or Staph. aureus Protein A. The fluorescent molecules

5 (fluorophores) can be detected by illumination with light of an appropriate excitation frequency and the resultant spectral emissions can be detected by electro-optical sensors or light microscopy.

A wide variety of fluorescent dyes are available and
10 offer a selection of excitation and emission spectra. It is possible to select fluorophores having emission spectra that are sufficiently different so as to permit multitarget detection and discrimination with multiple probes, wherein each probe species is linked to a different fluorophore.

15 Because the spectra of fluorophores can be discriminated on the basis of both narrow band excitation and selective detection of emission spectra, two or more distinct target species can be detected and resolved (Titus et al. (1982) J. Immunol. Methods 50: 193; Nederlof et al. (1989) Cytometry 10: 20; Ploem, J.S. (1971) Ann. NY Acad. Sci. 177: 414).

Unfortunately, detection methods which employ
fluorescent labels are of limited sensitivity for a variety of reasons. First, with conventional fluorophores it is
difficult to discriminate specific fluorescent signals from
25 nonspecific background signals. Most common fluorophores are aromatic organic molecules which have broad absorption and emission spectra, with the emission maximum red-shifted 50-100 nm to a longer wavelength than the excitation (i.e., absorption) wavelength. Typically, both the absorption and
30 emission bands are located in the UV/visible portion of the spectrum. Further, the lifetime of the fluorescence emission is usually short, on the order of 1 to 100 ns. Unfortunately, these general characteristics of organic dye fluorescence are also applicable to background signals which are contributed by
35 other reagents (e.g., fixative or serum), or autofluorescence or the sample itself (Jongkind et al. (1982) Exp. Cell Res. 138: 409; Aubin, J.E. (1979) J. Histochem. Cytochem. 27: 36).

Autofluorescence of optical lenses and reflected excitation light are additional sources of background noise in the visible spectrum (Beverloo et al. (1991) Cytometry 11: 784; Beverloo et al. (1992) Cytometry 13: 561). Therefore, the
5 limit of detection of specific fluorescent signal from typical fluorophores is limited by the significant background noise contributed by nonspecific fluorescence and reflected excitation light.

A second problem of organic dye fluorophores that
10 limits sensitivity is photolytic decomposition of the dye molecule (i.e., photobleaching). Thus, even in situations where background noise is relatively low, it is often not possible to integrate a weak fluorescent signal over a long detection time, since the dye molecules decompose as a
15 function of incident irradiation in the UV and near-UV bands.

However, because fluorescent labels are attractive for various applications, several alternative fluorophores having advantageous properties for sensitive detection have been proposed. One approach has been to employ organic dyes
20 comprising a phycobiliprotein acceptor molecule dye that emits in the far red or near infrared region of the spectrum where nonspecific fluorescent noise is reduced. Phycobiliproteins are used in conjunction with accessory molecules that effect a large Stokes shift via energy transfer mechanisms (U.S. Patent
25 No. 4,666,862; Oi et al. (1982) J. Cell. Biol. 93: 891). Phycobiliprotein labels reduce the degree of spectral overlap between excitation frequencies and emission frequencies. An alternative approach has been to use cyanine dyes which absorb in the yellow or red region and emit in the red or far red
30 where autofluorescence is reduced (Mujumbar et al. (1989) Cytometry 10: 11).

However, with both the phycobiliproteins and the cyanine dyes the emission frequencies are red-shifted (i.e., frequency downshifted) and emission lifetimes are short,
35 therefore background autofluorescence is not completely eliminated as a noise source. More importantly perhaps, phycobiliproteins and cyanine dyes possess several distinct

disadvantages: (1) emission in the red, far red, and near infrared region is not well-suited for detection by the human eye, hampering the use of phycobiliprotein and cyanine labels in optical fluorescence microscopy, (2) cyanines, phycobiliproteins, and the coupled accessory molecules (e.g., Azure A) are organic molecules susceptible to photobleaching and undergoing undesirable chemical interactions with other reagents, and (3) emitted radiation is down-converted, i.e., of longer wavelength(s) than the absorbed excitation radiation. For example, Azure A absorbs at 632 nm and emits at 645 nm, and allophycocyanin absorbs at 645 nm and emits at 655 nm, and therefore autofluorescence and background noise from scattered excitation light is not eliminated.

Another alternative class of fluorophore that has been proposed are the down-converting luminescent lanthanide chelates (Soini and Lovgren (1987) CRC Crit. Rev. Anal. Chem. 18: 105; Leif et al. (1977) Clin. Chem. 23: 1492; Soini and Hemmila (1979) Clin. Chem. 25: 353; Seveus et al. (1992) Cytometry 13: 329). Down-converting lanthanide chelates are inorganic phosphors which possess a large downward Stokes shift (i.e., emission maxima is typically at least 100 nm greater than absorption maxima) which aids in the discrimination of signal from scattered excitation light. Lanthanide phosphors possess emission lifetimes that are sufficiently long (i.e., greater than 1 μ s) to permit their use in time-gated detection methods which can reduce, but not totally eliminate, noise caused by shorter-lived autofluorescence and scattered excitation light. Further, lanthanide phosphors possess narrow-band emission, which facilitates wavelength discrimination against background noise and scattered excitation light, particularly when a laser excitation source is utilized (Reichstein et al. (1988) Anal. Chem. 60: 1069). Recently, enzyme-amplified lanthanide luminescence using down-converting lanthanide chelates has been proposed as a fluorescent labeling technique (Evangelista et al. (1991) Anal. Biochem. 197: 213; Gudgin-Templeton et al. (1991) Clin Chem. 37: 1506).

Until recently, down-converting lanthanide phosphors have had the significant disadvantage that their quantum efficiency in aqueous (oxygenated) solutions is so low as to render them unsuitable for cytochemical staining. Beverloo et al. (op.cit.) have described a particular down-converting lanthanide phosphor (yttrium oxysulfide activated with europium) that produces a signal in aqueous solutions which can be detected by time-resolved methods. Seveus et al. (op.cit.) have used down-converting europium chelates in conjunction with time-resolved fluorescence microscopy to reject the signal from prompt fluorescence and thereby reduce autofluorescence. Tanke et al. (U.S. Patent No. 5,043,265) report down-converting phosphor particles as labels for immunoglobulins and polynucleotides.

However, the down-converting lanthanide phosphor of Beverloo et al. and the europium chelate of Seveus et al. require excitation wavelength maxima that are in the ultraviolet range, and thus produce significant sample autofluorescence and background noise (e.g., serum and/or fixative fluorescence, excitation light scattering and refraction, etc.) that must be rejected (e.g., by filters or time-gated signal rejection). Further, excitation with ultraviolet irradiation damages nucleic acids and other biological macromolecules, posing serious problems for immunocytochemical applications where it is desirable to preserve the viability of living cells and retain cellular structures (e.g., FACS, cyto-architectural microscopy).

Laser scanning fluorescence microscopy has been used for two-photon excitation of a UV-excitable fluorescent organic dye, Hoechst 33258, using a stream of strongly focused laser pulses (Denk et al. (1990) Science 248: 73). The organic fluorophore used by Denk et al. was significantly photobleached by the intense, highly focused laser light during the course of imaging.

Thus, there exists a significant need in the art for labels and detection methods that permit sensitive optical and/or spectroscopic detection of specific label signal(s)

with essentially total rejection of nonspecific background noise, and which are compatible with intact viable cells and aqueous or airborne environments.

The references discussed herein are provided solely for their disclosure prior to the filing date of the present application. Nothing herein is to be construed as an admission that the inventors are not entitled to antedate such disclosure by virtue of prior invention.

SUMMARY OF THE INVENTION

The present invention provides labels, detection methods, and detection apparatus which permit ultrasensitive detection of cells, biological macromolecules, and other analytes, which can be used for multiple target detection and target discrimination. The up-converting labels of the invention permit essentially total rejection of non-specific background autofluorescence and are characterized by excitation and emitted wavelengths that are typically in the infrared or visible portions of the spectrum, respectively, and thus avoid the potentially damaging effects of ultraviolet radiation. The up-converting labels of the invention convert long-wavelength excitation radiation (e.g., near-IR) to emitted radiation at about one-half to one-third the wavelength of the excitation wavelength. Since background fluorescence in the visible range is negligible if near-IR excitation wavelengths are used, the use of up-converting labels provides essentially background-free detection of signal.

In brief, the invention provides the use of luminescent materials that are capable of multiphoton excitation and have upshifted emission spectra. In one embodiment of the invention, up-converting phosphors (i.e., which absorb multiple photons in a low frequency band and emit in a higher frequency band) are used as labels which can be linked to one or more probes, such as an immunoglobulin, polynucleotide, streptavidin, Protein A, receptor ligand, or other probe molecule. In an another embodiment, up-converting

organic dyes serve as the label. The organic dye labels and phosphor labels of the invention are highly compatible with automated diagnostic testing, microscopic imaging applications, and coded particle detection, among many other applications.

The nature of the invention provides considerable flexibility in the apparatus for carrying out the methods. As a general matter, the excitation source may be any convenient light source, including inexpensive near-infrared laser diodes or light-emitting diodes (LEDs), and the detector may be any convenient detector, such as a photodiode. In the case of a single reporter, the apparatus includes a laser diode capable of emitting light at one or more wavelengths in the reporter's excitation band and a detector that is sensitive to at least some wavelengths in the reporter's emission band. The laser light is preferably focused to a small region in the sample, and light emanating from that region is collected and directed to the detector. An electrical signal representing the intensity of light in the emission band provides a measure of the amount of reporter present. Depending on the detector's spectral response, it may be necessary to provide a filter to block the excitation light.

Simultaneous detection of multiple reporters is possible, at least where the reporters have different excitation bands or different emission bands. Where the excitation bands differ, multiple laser diodes emitting at respective appropriate wavelengths are combined using a wavelength division multiplexer or other suitable techniques, such as frequency labeling, frequency modulation, and lock-in detector device. If the emission bands are different (whether or not the excitation bands are different), light in the different emission bands is separated and sent to multiple detectors. If the emission bands overlap, a single detector may be used, but other detection techniques are used. One example is to use time multiplexing techniques so that only one reporter is emitting at a given time. Alternatively, the

different laser diodes can be modulated at different characteristic frequencies and lock-in detection performed.

Detection methods and detection apparatus of the present invention enable the ultrasensitive detection of up-
5 converting phosphors and up-converting organic dyes by exploiting what is essentially the total absence of background noise (e.g., autofluorescence, serum/fixative fluorescence, excitation light scatter) that are advantageous characteristics of up-converting labels. Some embodiments of
10 the invention utilize time-gated detection and/or wavelength-gated detection for optimizing detection sensitivity, discriminating multiple samples, and/or detecting multiple probes on a single sample. Phase-sensitive detection can also be used to provide discrimination between signal(s)
15 attributable to an up-converting phosphor and background noise (e.g. autofluorescence) which has a different phase shift.

Up-converting organic dyes, such as red-absorbing dyes, also can be used in an alternate embodiment that converts the photons absorbed by the dye into a transient
20 voltage that can be measured using electrodes and conventional electronic circuitry. After having undergone two-photon absorption the dye is ionized by additional photons from the light source (e.g., a laser) leading to short-lived molecular ions whose presence can be detected and quantified by
25 measuring the transient photoconductivity following the excitation irradiation. In this embodiment, resonant multiphoton ionization is used to provide a quantitative measurement of the number and/or concentration of dye molecules in a sample. Furthermore, essentially all photoions
30 formed in the irradiated sample contribute to the signal, whereas photons are emitted isotropically and only a fraction can be collected using optics. Measurement of the transient photocurrent effectively transfers the conversion of photons into an electronic signal that is readily measured with
35 relatively simple and inexpensive sensors such as electrodes.

In some embodiments, the present invention utilizes one or more optical laser sources for generating excitation

illumination of one or more discrete frequency(ies). In certain variations of the invention, laser irradiation of an up-converting label can modify the immediate molecular environment through laser-induced photochemical processes involving either direct absorption or energy transfer; such spatially-controlled deposition of energy can be used to produce localized damage and/or to probe the chemical environment of a defined location. In such embodiments, the up-converting label can preferably act as a photophysical catalyst.

The invention provides methods for producing targeted damage (e.g., catalysis) in chemical or biological materials, wherein a probe is employed to localize a linked up-converting label to a position near a targeted biological structure that is bound by the probe. The localized up-converting label is excited by one or more excitation wavelengths and emit at a shorter wavelength which may be directly cytotoxic or genotoxic (e.g., by producing free radicals such as superoxide, and/or by generating thymine-thymine dimers), or which may induce a local photolytic chemical reaction to produce reactive chemical species in the immediate vicinity of the label, and hence in the vicinity of the targeted biological material. Thus, targeting probes labeled with one or more up-converting labels (e.g., an up-converting inorganic phosphor) may be used to produce targeted damage to biological structures, such as cells, tissues, neoplasms, vasculature, or other anatomical or histological structures.

Embodiments of the present invention also include up-converting phosphors which can also be excited by an electron beam or other beam of energetic radiation of sufficient energy and are cathodoluminescent. Such electron-stimulated labels afford novel advantages in eliminating background in ultrasensitive biomolecule detection methods. Typically, stimulation of the up-converting phosphor with at least two electrons is employed to generate a visible-light or UV band emission.

The invention also provides for the simultaneous detection of multiple target species by exploiting the multiphoton excitation and subsequent background-free fluorescence detection of several up-converting phosphors or up-converting dyes. In one embodiment, several phosphors/dyes are selected which have overlapping absorption bands which allow simultaneous excitation at one wavelength (or in a narrow bandwidth), but which vary in emission characteristics such that each probe-label species is endowed with a distinguishable fluorescent "fingerprint." By using various methods and devices, the presence and concentration of each of the phosphors or dyes can be determined.

The invention also provides biochemical assay methods for determining the presence and concentration of one or more analytes, typically in solution. The assay methods employ compositions of probes labeled with up-converting phosphors and/or up-converting dyes and apparatus for magnetically and/or optically trapping particles that comprise the analyte and the labeled probe. In one embodiment, a sandwich assay is performed, wherein an immobilized probe, immobilized on a particle, binds to a predetermined analyte, producing an immobilization of the bound analyte on the particle; a second probe, labeled with an up-converting label can then bind to the bound analyte to produce a bound sandwich complex containing an up-converting label bound to a particle. By combining different probe-label combinations, particles of various sizes, colors, and/or shapes with distinct immobilized probe(s), and/or various excitation wavelengths, it is possible to perform multiple assays essentially simultaneously or contemporaneously. This multiplex advantage affords detection and quantitation of multiple analyte species in a single sample. The assay methods are also useful for monitoring the progress of a reaction, such as a physical, chemical, biochemical, or immunological reaction, including binding reactions. For example, the invention may be used to monitor the progress of ligand-binding reactions, polynucleotide hybridization reactions, including

hybridization kinetics and thermodynamic stability of hybridized polynucleotides.

The invention also provides methods, up-converting labels, and compositions of labeled binding reagents for performing fluorescence-activated cell sorting (FACS) by flow cytometry using excitation radiation that is in the infrared portion of the spectrum and does not significantly damage cells. This provides a significant advantage over present FACS methods which rely on excitation illumination in the ultraviolet portion of the spectrum, including wavelengths which are known to produce DNA lesions and damage cells.

The invention also provides compositions comprising at least one fluorescent organic dye molecule attached to an inorganic up-converting phosphor. The fluorescent organic dye molecule is selected from the group consisting of: rhodamines, cyanines, xanthenes, acridines, oxazines, porphyrins, and phthalocyanines, and may optionally be complexed with a heavy metal. The fluorescent organic dye may be adsorbed to the inorganic up-converting phosphor crystal and/or may be covalently attached to a coated inorganic up-converting phosphor, a derivatized vitroc ceramic up-converting phosphor, or a microencapsulated inorganic up-converting phosphor.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is an optical and electronic block diagram illustrating representative apparatus for performing diagnostics on a sample according to the present invention;

Fig. 2A shows apparatus for implementing phase sensitive detection in the context of a single channel;

Fig. 2B shows apparatus where first and second laser diodes are modulated by signals from waveform generators;

Fig. 3 shows apparatus for performing gated detection;

Fig. 4 shows an apparatus for performing diagnostics on a sample using first and second reporters excitation bands

centered at λ_1 and λ_2 , respectively, and having overlapping emission bands near λ_3 ;

Fig. 5A, 5B, 5C show schematically energy state transitions in multi-photon excitation schemes.

5 Fig. 6 shows a miniaturized instrument using a hand-held probe;

Fig. 7A shows the use of a charge-coupled device (CCD) array used to detect emissions from a large plurality of binding sites;

10 Fig. 7B shows the CCD array used in conjunction with a lens array;

Fig. 8 shows an embodiment using optical trapping;

Fig. 9 shows schematically dye coating and encapsulation of an up-converting phosphor particle;.

15 Fig. 10 shows schematically an apparatus for determining particle velocity and hydrodynamic or aerodynamic properties of a target;

Fig. 11 is a phosphor emission spectrum of sodium yttrium fluoride-ytterbium/erbium up-converting phosphor with an excitation laser source at a wavelength maximum of 977.2 nm; emission maximum is about 541.0 nm;

20 Fig. 12 is an excitation scan of the sodium yttrium fluoride-ytterbium/erbium phosphor excitation spectrum, with emission collection window set at 541.0 nm;

25 Fig. 13 is a time-decay measurement of the phosphor luminescence at 541 nm after termination of excitation illumination for sodium yttrium fluoride-ytterbium/erbium;

Fig. 14 shows the phosphor emission intensity as a function of excitation illumination intensity for a sodium yttrium fluoride-ytterbium/erbium phosphor;

30 Fig. 15 shows effective single-photon phosphorescence cross-section for 0.3 μm particles of $\text{Na}(\text{Y}_{0.8}\text{Yb}_{0.12}\text{Er}_{0.08})\text{F}_4$ following excitation with 200W/cm² at 970nm.

35 Fig. 16 shows size-dependence of phosphorescence cross-section for $\text{Na}(\text{Y}_{0.8}\text{Yb}_{0.12}\text{Er}_{0.08})\text{F}_4$ particles.

Fig. 17A shows a fluorescence scan of an up-converting phosphor reporter in Hepes-buffered saline induced by excitation with a 970-nm laser source;

Fig. 17B shows a fluorescence spectrum scan of an up-converting phosphor reporter coated with streptavidin in Hepes-buffered saline induced by excitation with a 970-nm laser source;

Fig 18A shows an excitation spectrum scan of an up-converting phosphor reporter in Hepes-buffered saline with monochromatic detection of emission at 541 nm;

Fig 18B shows an excitation spectrum scan of an up-converting phosphor reporter coated with streptavidin in Hepes-buffered saline with monochromatic detection of emission at 541 nm;

Fig. 19 shows the integrated signal obtained from samples of $(Y_{0.86}Yb_{0.08}Er_{0.06})_2O_2S$ showing the relationship between phosphor concentration and up-converted signal;

Fig. 20 shows schematically one embodiment of an sandwich immunoassay for detecting an analyte in a solution by binding the analyte (e.g., an antigen target) to a biotinylated antibody and to an immobilized antibody, wherein the analyte forms a sandwich complex immobilized on a solid substrate superparamagnetic microbead; and

Fig. 21 shows schematically detection and discrimination of two cell surface antigens with specific antibodies labeled with two phosphors with distinct phosphorescence characteristics.

Fig. 22 shows a schematic of an apparatus for phase-sensitive detection.

Fig. 23 show a schematic of a competitive homogeneous assay using phosphors as labels and fiber optic illumination at a capture surface.

Fig. 24 show a schematic of a competitive homogeneous antigen capture assay using phosphors as labels and a convergent illumination beam focused on the capture surface.

Fig. 25 show a schematic of a homogeneous immunoprecipitation assay using phosphors as labels and a convergent illumination beam focused on the capture surface wherein the capture surface collects immunoprecipitates.

5

DESCRIPTION OF SPECIFIC EMBODIMENTS

Definitions

Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. Although any methods and materials similar or equivalent to those described herein can be used in the practice or testing of the present invention, the preferred methods and materials are described. For purposes of the present invention, the following terms are defined below.

As used herein, "label" refers to a chemical substituent that produces, under appropriate excitation conditions, a detectable optical signal. The optical signal produced by an excited label is typically electromagnetic radiation in the near-infrared, visible, or ultraviolet portions of the spectrum. The labels of the invention are up-converting labels, which means that the chemical substituent absorbs at least two photons at an excitation frequency and subsequently emits electromagnetic energy at an emission frequency higher than the excitation frequency. Thus, there is generally a significant Stokes shift between the original excitation frequency and the final emission frequency. A label is generally attached to a probe to serve as a reporter that indicates the presence and/or location of probe. The invention encompasses organic and inorganic up-converting labels, but preferably employs up-converting inorganic lanthanide phosphors as labels. Thus, a typical label of the invention is a submicron-size up-converting lanthanide phosphor particle.

As used herein, a "probe" refers to a binding component which binds preferentially to one or more targets (e.g, antigenic epitopes, polynucleotide sequences,

macromolecular receptors) with an affinity sufficient to permit discrimination of labeled probe bound to target from nonspecifically bound labeled probe (i.e., background). Generally, the probe-target binding is a non-covalent interaction with a binding affinity (K_D) of at least about $1 \times 10^6 \text{ M}^{-1}$, preferably with at least about $1 \times 10^7 \text{ M}^{-1}$, and more preferably with an affinity of at least about $1 \times 10^8 \text{ M}^{-1}$ or greater. Antibodies typically have a binding affinity for cognate antigen of about $1 \times 10^{10} \text{ M}^{-1}$ or more. For example but not limitation, probes of the invention include: antibodies, polypeptide hormones, polynucleotides, streptavidin, *Staphylococcus aureus* protein A, receptor ligands (e.g., steroid or polypeptide hormones), leucine zipper polypeptides, lectins, antigens (polypeptide, carbohydrate, nucleic acid, and hapten epitopes), and others.

As used herein, a "probe-label conjugate" and a "labeled probe" refer to a combination comprising a label attached to a probe. In certain embodiments, more than one label substituent may be attached to a probe. Alternatively, in some embodiments more than one probe may be attached to a label (e.g., multiple antibody molecules may be attached to a submicron-size inorganic up-converting phosphor bead). Various attachment chemistries can be employed to link a label to a probe, including, but not limited to, the formation of: covalent bonds, hydrogen bonds, ionic bonds, electrostatic interactions, and surface tension (phase boundary) interactions. Attachment of label can also involve incorporation of the label into or onto microspheres, microparticles, immunobeads, and superparamagnetic magnetic beads (Polysciences, Inc., Warrington, Pennsylvania; Bangs Laboratories, Inc. 979 Keystone Way, Carmel, IN 46032). For example, inorganic up-converting phosphor particles can be encapsulated in microspheres that are composed of polymer material that is essentially transparent or translucent in the wavelength range(s) of the excitation and emitted electromagnetic radiation (U.S. Patent 5,132,242, incorporated herein by reference). Such microspheres can be functionalized

by surface derivatization with one or more reactive groups (e.g., carboxylate, amino, hydroxylate, or polyacrolein) for covalent attachment to a probe, such as a protein. Probe-label conjugates can also comprise a phosphor chelate.

5 As used herein, the term "target" and "target analyte" refer to the object(s) that is/are assayed for by the methods of the invention. For example but not limitation, targets can comprise polypeptides (e.g., hGH, insulin, albumin), glycoproteins (e.g., immunoglobulins,
10 thrombomodulin, γ -glutamyltranspeptidase; Goodspeed et al. (1989), Gene 76: 1), lipoproteins, viruses, microorganisms (e.g., pathogenic bacteria, yeasts), polynucleotides (e.g., cellular genomic DNA, RNA in a fixed histological specimen for in situ hybridization, DNA or RNA immobilized on a nylon or
15 nitrocellulose membrane, viral DNA or RNA in a tissue or biological fluid), and pharmaceuticals (i.e., prescribed or over-the-counter drugs listed in the Physicians Drug Reference and/or Merck Manual, or illegal substances such as intoxicants or anabolic steroids).

20 As used herein, the term "antibody" refers to a protein consisting of one or more polypeptides substantially encoded by immunoglobulin genes. The recognized immunoglobulin genes include the kappa, lambda, alpha, gamma (IgG₁, IgG₂, IgG₃, IgG₄), delta, epsilon and mu constant region
25 genes, as well as the myriad immunoglobulin variable region genes. Full-length immunoglobulin "light chains" (about 25 Kd or 214 amino acids) are encoded by a variable region gene at the NH₂-terminus (about 110 amino acids) and a kappa or lambda constant region gene at the COOH-terminus. Full-length
30 immunoglobulin "heavy chains" (about 50 Kd or 446 amino acids), are similarly encoded by a variable region gene (about 116 amino acids) and one of the other aforementioned constant region genes, e.g., gamma (encoding about 330 amino acids). One form of immunoglobulin constitutes the basic structural
35 unit of an antibody. This form is a tetramer and consists of two identical pairs of immunoglobulin chains, each pair having one light and one heavy chain. In each pair, the light and

heavy chain variable regions are together responsible for binding to an antigen, and the constant regions are responsible for the antibody effector functions. In addition to antibodies, immunoglobulins may exist in a variety of other forms including, for example, Fv, Fab, and F(ab')₂, as well as bifunctional hybrid antibodies (e.g., Lanzavecchia et al., Eur. J. Immunol. 17, 105 (1987)) and in single chains (e.g., Huston et al., Proc. Natl. Acad. Sci. U.S.A., 85, 5879-5883 (1988) and Bird et al., Science, 242, 423-426 (1988)). (See, generally, Hood et al., "Immunology", Benjamin, N.Y., 2nd ed. (1984), and Hunkapiller and Hood, Nature, 323, 15-16 (1986)). Thus, not all immunoglobulins are antibodies. (See, U.S.S.N. 07/634,278, which is incorporated herein by reference, and Co et al. (1991) Proc. Natl. Acad. Sci. (U.S.A.) 88: 2869, which is incorporated herein by reference).

As used herein, "probe polynucleotide" refers to a polynucleotide that specifically hybridizes to a predetermined target polynucleotide. For example but not limitation, a probe polynucleotide may be a portion of a cDNA corresponding to a particular mRNA sequence, a portion of a genomic clone, a synthetic oligonucleotide having sufficient sequence homology to a known target sequence (e.g., a telomere repeat TTAGGG or an Alu repetitive sequence) for specific hybridization, a transcribed RNA (e.g., from an SP6 cloning vector insert), or a polyamide nucleic acid (Nielsen et al. (1991) Science 254: 1497). Various target polynucleotides may be detected by hybridization of a labeled probe polynucleotide to the target sequence(s). For example but not limitation, target polynucleotides may be: genomic sequences (e.g., structural genes, chromosomal repeated sequences, regulatory sequences, etc.), RNA (e.g., mRNA, hnRNA, rRNA, etc.), pathogen sequences (e.g., viral or mycoplasmal DNA or RNA sequences), or transgene sequences.

"Specific hybridization" is defined herein as the formation of hybrids between a probe polynucleotide and a target polynucleotide, wherein the probe polynucleotide preferentially hybridizes to the target DNA such that, for

example, at least one discrete band can be identified on a Southern blot of DNA prepared from eukaryotic cells that contain the target polynucleotide sequence, and/or a probe polynucleotide in an intact nucleus localizes to a discrete chromosomal location characteristic of a unique or repetitive sequence. In some instances, a target sequence may be present in more than one target polynucleotide species (e.g., a particular target sequence may occur in multiple members of a gene family or in a known repetitive sequence). It is evident that optimal hybridization conditions will vary depending upon the sequence composition and length(s) of the targeting polynucleotide(s) and target(s), and the experimental method selected by the practitioner. Various guidelines may be used to select appropriate hybridization conditions (see, Maniatis et al., Molecular Cloning: A Laboratory Manual (1989), 2nd Ed., Cold Spring Harbor, N.Y. and Berger and Kimmel, Methods in Enzymology, Volume 152, Guide to Molecular Cloning Techniques (1987), Academic Press, Inc., San Diego, CA., Dunn et al. (1989) J. Biol. Chem. 264: 13057 and Goodspeed et al. (1989) Gene 76: 1.

As used herein, the term "label excitation wavelength" refers to an electromagnetic radiation wavelength that, when absorbed by an up-converting label, produces a detectable fluorescent emission from the up-converting label, wherein the fluorescent emission is of a shorter wavelength (i.e., higher frequency radiation) than the label excitation wavelength. As used herein, the term "label emission wavelength" refers to a wavelength that is emitted from an up-converting label subsequent to, or contemporaneously with, illumination of the up-converting label with one or more excitation wavelengths; label emission wavelengths of up-converting labels are shorter (i.e., higher frequency radiation) than the corresponding excitation wavelengths. Both label excitation wavelengths and label emission wavelengths are characteristic to individual up-converting label species, and are readily determined by performing simple excitation and emission scans.

Invention Overview

The subject invention encompasses fluorescent labels that are excited by an excitation wavelength and subsequently emit electromagnetic radiation at up-shifted frequencies (i.e., at higher frequencies than the excitation radiation).

In accordance with the present invention, labels comprising up-converting inorganic phosphors and/or up-converting organic dyes are provided for various applications. The up-converting labels of the invention may be attached to one or more probe(s) to serve as a reporter (i.e., a detectable marker) of the location of the probe(s). The up-converting labels can be attached to various probes, such as antibodies, streptavidin, protein A, polypeptide ligands of cellular receptors, polynucleotide probes, drugs, antigens, toxins, and others. Attachment of the up-converting label to the probe can be accomplished using various linkage chemistries, depending upon the nature of the specific probe. For example but not limitation, microcrystalline up-converting lanthanide phosphor particles may be coated with a polycarboxylic acid (e.g., Additon XW 330, Hoechst, Frankfurt, Germany) during milling and various proteins (e.g., immunoglobulin, streptavidin or protein A) can be physically adsorbed to the surface of the phosphor particle (Beverloo et al. (1991) op.cit., which is incorporated herein by reference). Alternatively, various inorganic phosphor coating techniques can be employed including, but not limited to: spray drying, plasma deposition, and derivatization with functional groups (e.g., -COOH, -NH₂, -CONH₂) attached by a silane coupling agent to -SiOH moieties coated on the phosphor particle or incorporated into a vitroceramic phosphor particle comprising silicon oxide(s) and up-converting phosphor compositions. Vitroceramic phosphor particles can be aminated with, for example, aminopropyltriethoxysilane for the purpose of attaching amino groups to the vitroceramic surface on linker molecules, however other omega-functionalized silanes can be substituted to attach alternative functional groups. Probes, such as proteins or polynucleotides may then be

directly attached to the vitroc ceramic phosphor by covalent linkage, for example through siloxane bonds or through carbon-carbon bonds to linker molecules (e.g., organofunctional silylating agents) that are covalently bonded to or adsorbed to the surface of a phosphor particle.

Microcrystalline up-converting phosphor particles are typically smaller than about 3 microns in diameter, preferably less than about 1 micron in diameter (i.e., submicron), and more preferably are 0.1 to 0.3 microns or less in diameter. It is generally most preferred that the phosphor particles are as small as possible while retaining sufficient quantum conversion efficiency to produce a detectable signal; however, for any particular application, the size of the phosphor particle(s) to be used should be selected at the discretion of the practitioner. For instance, some applications (e.g., detection of a non-abundant cell surface antigen) may require a highly sensitive phosphor label that need not be small but must have high conversion efficiency and/or absorption cross-section, while other applications (e.g., detection of an abundant nuclear antigen in a permeabilized cell) may require a very small phosphor particle that can readily diffuse and penetrate subcellular structures, but which need not have high conversion efficiency. Therefore, the optimal size of inorganic phosphor particle is application dependent and is selected by the practitioner on the basis of quantum efficiency data for the various phosphors of the invention. Such conversion efficiency data may be obtained from available sources (e.g., handbooks and published references) or may be obtained by generating a standardization curve measuring quantum conversion efficiency as a function of particle size. In some applications, such as those requiring highly sensitive detection of small phosphor particles, infrared laser diodes are preferably selected as an excitation source.

Although the properties of the up-converting phosphors will be described in detail in a later section, it is useful to outline the basic mechanisms involved. Up-

conversion has been found to occur in certain materials containing rare-earth ions in certain crystal materials. For example, ytterbium and erbium act as an activator couple in a phosphor host material such as barium-yttrium-fluoride. The
5 ytterbium ions act as the absorber, and transfer energy non-radiatively to excite the erbium ions. The emission is thus characteristic of the erbium ion's energy levels.

Up-Converting Microcrystalline Phosphors

10 Although the invention can be practiced with a variety of up-converting inorganic phosphors, it is believed that the preferred embodiment(s) employ one or more phosphors derived from one of several different phosphor host materials, each doped with at least one activator couple. Suitable
15 phosphor host materials include: sodium yttrium fluoride (NaYF_4), lanthanum fluoride (LaF_3), lanthanum oxysulfide, yttrium oxysulfide, yttrium fluoride (YF_3), yttrium gallate, yttrium aluminum garnet, gadolinium fluoride (GdF_3), barium yttrium fluoride (BaYF_5 , BaY_2F_8), and gadolinium oxysulfide.
20 Suitable activator couples are selected from: ytterbium/erbium, ytterbium/thulium, and ytterbium/holmium. Other activator couples suitable for up-conversion may also be used. By combination of these host materials with the activator couples, at least three phosphors with at least
25 three different emission spectra (red, green, and blue visible light) are provided. Generally, the absorber is ytterbium and the emitting center can be selected from: erbium, holmium, terbium, and thulium; however, other up-converting phosphors of the invention may contain other absorbers and/or emitters.
30 The molar ratio of absorber: emitting center is typically at least about 1:1, more usually at least about 3:1 to 5:1, preferably at least about 8:1 to 10:1, more preferably at least about 11:1 to 20:1, and typically less than about 250:1, usually less than about 100:1, and more usually less than
35 about 50:1 to 25:1, although various ratios may be selected by the practitioner on the basis of desired characteristics (e.g., chemical properties, manufacturing efficiency,

absorption cross-section, excitation and emission wavelengths, quantum efficiency, or other considerations). The ratio(s) chosen will generally also depend upon the particular absorber-emitter couple(s) selected, and can be calculated
5 from reference values in accordance with the desired characteristics.

The optimum ratio of absorber (e.g., ytterbium) to the emitting center (e.g., erbium, thulium, or holmium) varies, depending upon the specific absorber/emitter couple.
10 For example, the absorber:emitter ratio for Yb:Er couples is typically in the range of about 20:1 to about 100:1, whereas the absorber:emitter ratio for Yb:Tm and Yb:Ho couples is typically in the range of about 500:1 to about 2000:1. These
15 different ratios are attributable to the different matching energy levels of the Er, Tm, or Ho with respect to the Yb level in the crystal. For most applications, up-converting phosphors may conveniently comprise about 10-30% Yb and either: about 1-2% Er, about 0.1-0.05% Ho, or about 0.1-0.05% Tm, although other formulations may be employed.

20 Some embodiments of the invention employ inorganic phosphors that are optimally excited by infrared radiation of about 950 to 1000 nm, preferably about 960 to 980 nm. For example but not limitation, a microcrystalline inorganic phosphor of the formula $YF_3:Yb_{0.10}Er_{0.01}$ exhibits a luminescence
25 intensity maximum at an excitation wavelength of about 980 nm. Inorganic phosphors of the invention typically have emission maxima that are in the visible range. For example, specific activator couples have characteristic emission spectra: ytterbium-erbium couples have emission maxima in the red or
30 green portions of the visible spectrum, depending upon the phosphor host; ytterbium-holmium couples generally emit maximally in the green portion, ytterbium-thulium typically have an emission maximum in the blue range, and ytterbium-terbium usually emit maximally in the green range. For
35 example, $Y_{0.80}Yb_{0.19}Er_{0.01}F_2$ emits maximally in the green portion of the spectrum.

Although up-converting inorganic phosphor crystals of various formulae are suitable for use in the invention, the following formulae, provided for example and not to limit the invention, are generally suitable:

5

$\text{Na}(\text{Y}_x\text{Yb}_y\text{Er}_z)\text{F}_4$: x is 0.7 to 0.9, y is 0.09 to 0.29, and z is 0.05 to 0.01;

10 $\text{Na}(\text{Y}_x\text{Yb}_y\text{Ho}_z)\text{F}_4$: x is 0.7 to 0.9, y is 0.0995 to 0.2995, and z is 0.0005 to 0.001; and

$\text{Na}(\text{Y}_x\text{Yb}_y\text{Tm}_z)\text{F}_4$: x is 0.7 to 0.9, y is 0.0995 to 0.2995, and z is 0.0005 to 0.001.

15 $(\text{Y}_x\text{Yb}_y\text{Er}_z)\text{O}_2\text{S}$: x is 0.7 to 0.9, y is 0.05 to 0.12; z is 0.05 to 0.12.

$(\text{Y}_{0.86}\text{Yb}_{0.08}\text{Er}_{0.06})_2\text{O}_3$ is a relatively efficient up-converting phosphor material.

20

For exemplification, but not to limit the invention, ytterbium(Yb)-erbium(Er)-doped yttrium oxysulfides luminesce in the green after excitation at 950 nm. These are non-linear phosphors, in that the ytterbium acts as an "antenna" (absorber) for two 950 nm photons and transfers its energy to erbium which acts as an emitter (activator). The critical grain size of the phosphor is given by the quantum yield for green emission and the doping level of both Yb and Er, which is generally in the range of about 1 to 10 percent, more usually in the range of about 2 to 5 percent. A typical Yb:Er phosphor crystal comprises about 10-30% Yb and about 1-2% Er. Thus, a phosphor grain containing several thousand formula units ensures the emission of at least one or more photons during a typical laser irradiation time. However, the nonlinear relationship between absorption and emission indicates that intense illumination at the excitation wavelength(s) may be necessary to obtain satisfactory signal

25
30
35

in embodiments employing very small phosphor particles (i.e., less than about 0.3 μm). Additionally, it is usually desirable to increase the doping levels of activator/emitter couples for producing very small phosphor particles so as to maximize quantum conversion efficiency.

Inorganic microcrystalline phosphors with rare earth activators generally have narrow absorption and line emission spectra. The line emission spectra are due to $f-f$ transitions within the rare earth ion. These are shielded internal transitions which result in narrow line emission.

In certain applications, such as where highly sensitive detection is required, intense illumination can be provided by commercially available sources, such as infrared laser sources (e.g., continuous wave (CW) or pulsed semiconductor laser diodes). For example, in applications where the microcrystalline phosphor particle must be very small and the quantum conversion efficiency is low, intense laser illumination can increase signal and decrease detection times. Alternatively, some applications of the invention may require phosphor compositions that have inherently low quantum conversion efficiencies (e.g., low doping levels of activator couple), but which have other desirable characteristics (e.g., manufacturing efficiency, ease of derivatization, etc.); such low efficiency up-converting phosphors are preferably excited with laser illumination at a frequency at or near (i.e., within about 25 to 75 nm) an absorption maximum of the material. The fact that no other light is generated in the system other than from the up-converting phosphor allows for extremely sensitive signal detection, particularly when intense laser illumination is used as the source of excitation radiation. Thus, the unique property of up-conversion of photon energy by up-converting phosphors makes possible the detection of very small particles of microcrystalline inorganic phosphors. For practical implementation of phosphors as ultrasensitive reporters, particularly as intracellular reporters, it is essential that the grain size of the phosphor be as small as practicable (typically less

than about 0.3 to 0.1 μm), for which laser-excited up-converting phosphors are well-suited.

For example, various phosphor material compositions capable of up-conversion are suitable for use in the invention
5 are shown in Table I.

Table I: Phosphor Material Compositions

	<u>Host Material</u>	<u>Absorber Ion</u>	<u>Emitter Ion</u>	<u>Color</u>
	<i>Oxysulfides (O_2S)</i>			
10	$\text{Y}_2\text{O}_2\text{S}$	Ytterbium	Erbium	Green
	$\text{Gd}_2\text{O}_2\text{S}$	Ytterbium	Erbium	Red
	$\text{La}_2\text{O}_2\text{S}$	Ytterbium	Holmium	Green
	<i>Oxyhalides (OX_y)</i>			
15	YOF	Ytterbium	Thulium	Blue
	Y_3OCl_7	Ytterbium	Terbium	Green
	<i>Fluorides (F_x)</i>			
20	YF_3	Ytterbium	Erbium	Red
	GdF_3	Ytterbium	Erbium	Green
	LaF_3	Ytterbium	Holmium	Green
	NaYF_3	Ytterbium	Thulium	Blue
	BaYF_5	Ytterbium	Thulium	Blue
25	BaY_2F_8	Ytterbium	Terbium	Green
	<i>Gallates (Ga_xO_y)</i>			
	YGaO_3	Ytterbium	Erbium	Red
	$\text{Y}_3\text{Ga}_5\text{O}_{12}$	Ytterbium	Erbium	Green
30	<i>Silicates (Si_xO_y)</i>			
	YSi_2O_5	Ytterbium	Holmium	Green
	YSi_3O_7	Ytterbium	Thulium	Blue

In addition to the materials shown in Table I and variations
35 thereof, aluminates, phosphates, and vanadates can be suitable
phosphor host materials. In general, when silicates are used
as a host material, the conversion efficiency is relatively
low. In certain uses, hybrid up-converting phosphor crystals
may be made (e.g., combining one or more host material and/or
40 one or more absorber ion and/or one or more emitter ion).

Preparation of Inorganic Phosphor Labels

Techniques and methods for manufacture of inorganic
phosphors has been described in the art. Up-converting
45 phosphor crystals can be manufactured by those of ordinary

skill in the art by various published methods, including but not limited to the following: Yocom et al. (1971)

Metallurgical Transactions 2: 763; Kano et al. (1972) J. Electrochem. Soc., p. 1561; Wittke et al. (1972) J. Appl.

- 5 Physics 43: 595; Van Uitert et al. (1969) Mat. Res. Bull. 4: 381; which are incorporated herein by reference. Other references which may be referred to are: Jouart JP and Mary G (1990) J. Luminescence 46: 39; McPherson GL and Meyerson SL (1991) Chem. Phys. Lett. (April) p.325; Oomen et al. (1990) J.
10 Luminescence 46: 353; NI H and Rand SC (1991) Optics Lett. 16 (Sept.); McFarlane RA (1991) Optics Lett. 16 (Sept.); Koch et al. (1990) Appl. Phys. Lett. 56: 1083; Silversmith et al. (1987) Appl. Phys. Lett. 51: 1977; Lenth W and McFarlane RM (1990) J. Luminescence 45: 346; Hirao et al. (1991) J. Non-
15 crystalline Solids 135: 90; McFarlane et al. (1988) Appl. Phys. Lett. 52: 1300, incorporated herein by reference).

In general, inorganic phosphor particles are milled to a desired average particle size and distribution by conventional milling methods known in the art, including
20 milling in a conventional barrel mill with zirconia and/or alumina balls for periods of up to about 48 hours or longer. Phosphor particles used in binding assays are typically about 3.0 to 0.01 μm in diameter (or along the long axis if non-spherical), more usually about 2.0 to 0.1 μm in size, and more
25 conveniently about 1.0 to 0.3 μm in size, although phosphor particles larger or smaller than these dimensions may be preferred for certain embodiments. Phosphor particle size is selected by the practitioner on the basis of the desired characteristics and in accordance with the guidelines provided
30 herein. Fractions having a particular particle size range may be prepared by sedimentation, generally over an extended period (i.e., a day or more) with removal of the desired size range fraction after the appropriate sedimentation time. The sedimentation process may be monitored, such as with a Horiba
35 Particle Analyzer.

Phosphor particles can be coated or treated with surface-active agents (e.g., anionic surfactants such as

Aerosol OT) during the milling process or after milling is completed. For example, particles may be coated with a polycarboxylic acid (e.g., Additon XW 330, Hoechst, Frankfurt, Germany or Tamol, see Beverloo et al. (1992) op.cit.) during
5 milling to produce a stable aqueous suspension of phosphor particles, typically at about pH 6-8. The pH of an aqueous solution of phosphor particles can be adjusted by addition of a suitable buffer and titration with acid or base to the desired pH range. Depending upon the chemical nature of the
10 coating, some minor loss in conversion efficiency of the phosphor may occur as a result of coating, however the power available in a laser excitation source can compensate for such reduction in conversion efficiency and ensure adequate phosphor emission.

15 In general, preparation of inorganic phosphor particles and linkage to binding reagents is performed essentially as described in Beverloo et al. (1992) op.cit., and Tanke U.S. Patent 5,043,265.

Frequently, such as with phosphors having an
20 oxysulfide host material, the phosphor particles are preferably dispersed in a polar solvent, such as acetone or DMSO and the like, to generate a substantially monodisperse emulsion (e.g., for a stock solution). Aliquots of the monodisperse stock solution may be further diluted into an
25 aqueous solution (e.g., a solution of avidin in buffered water or buffered saline).

Binding Assays

Up-converting phosphors and up-converting organic
30 dyes are used as reporters (i.e., detectable markers) to label binding reagents, either directly or indirectly, for use in binding assays to detect and quantitate the presence of analyte(s) in a sample. Binding reagents are labeled directly by attachment to up-converting reporters (e.g., surface
35 adsorption, covalent linkage). Binding reagents which can be directly labeled include, but are not limited to: primary antibodies (i.e., which bind to a target analyte), secondary

antibodies (i.e., which bind to a primary antibody or prosthetic group, such as biotin or digoxigenin), *Staphylococcus aureus* Protein A, polynucleotides, streptavidin, and receptor ligands. Binding reagents can also be indirectly
5 labeled; thus, a primary antibody (e.g., a rabbit anti-erb-B antibody) can be indirectly labeled by noncovalent binding to a directly labeled second antibody (e.g., a goat anti-rabbit antibody linked to an up-converting inorganic phosphor). Quantitative detection of the analyte-probe complex may be
10 conducted in conjunction with proper calibration of the assay for each probe employed. A probe is conveniently detected under saturating excitation conditions using, for example, a laser source or focused photodiode source for excitation illumination.

15 Specific binding assays are commonly divided into homogeneous and heterogeneous assays. In a homogeneous assay, the signal emitted by the bound labeled probe is different from the signal emitted by the unbound labeled probe, hence the two can be distinguished without the need for a physical
20 separation step. In heterogeneous assays, the signal emitted from the bound and unbound labeled probes is identical, hence the two must be physically separated in order to distinguish between them. The classical heterogeneous specific binding assay is the radioimmunoassay (RIA) (Yalow et al. (1978)
25 Science 200: 1245, which is incorporated herein by reference). Other heterogeneous binding assays include the radioreceptor assay (Cuatrecasas et al. (1974) Ann. Rev. Biochem. 43: 109), the sandwich radioimmunoassay (U.S. Patent 4,376,110, which is incorporated herein by reference), and the antibody/lectin
30 sandwich assay (EP 0 166 623, which is incorporated herein by reference). Heterogeneous assays are usually preferred, and are generally more sensitive and reliable than homogeneous assays.

Whether a tissue extract is made or a biological
35 fluid sample is used, it is often desirable to dilute the sample in one or more diluents that do not substantially interfere with subsequent assay procedures. Generally,

suitable diluents are aqueous solutions containing a buffer system (e.g., 50 mM NaH_2PO_4 or 5-100 mM Tris, pH4-pH10), non-interfering ionic species (5-500 mM KCl or NaCl, or sucrose), and optionally a nonionic detergent such as Tween. When the sample to be analyzed is affixed to a solid support, it is usually desirable to wash the sample and the solid support with diluent prior to contacting with probe. The sample, either straight or diluted, is then analyzed for the diagnostic analyte.

In the general method of the invention, an analyte in a sample is detected and quantified by contacting the sample with a probe-label conjugate that specifically or preferentially binds to an analyte to form a bound complex, and then detecting the formation of bound complex, typically by measuring the presence of label present in the bound complexes. A probe-label conjugate can include a directly labeled analyte-binding reagent (e.g., a primary antibody linked to an up-converting phosphor) and/or an indirectly labeled analyte-binding reagent (e.g., a primary antibody that is detected by a labeled second antibody, or a biotinylated polynucleotide that is detected by labeled streptavidin). The bound complex(es) are typically isolated from unbound probe-label conjugate(s) prior to detection of label, usually by incorporating at least one washing step, so as to remove background signal attributable to label present in unbound probe-label conjugate(s). Hence, it is usually desirable to incubate probe-label conjugate(s) with the analyte sample under binding conditions for a suitable binding period.

Binding conditions vary, depending upon the nature of the probe-label conjugate, target analyte, and specific assay method. Thus, binding conditions will usually differ if the probe is a polynucleotide used in an in situ hybridization, in a Northern or Southern blot, or in solution hybridization assay. Binding conditions will also be different if the probe is an antibody used in an in situ histochemical staining method or a Western blot (Towbin et al. (1979) Proc. Natl. Acad. Sci. (U.S.A.) 76: 4350, incorporated

herein by reference). In general, binding conditions are selected in accordance with the general binding methods known in the art. For example, but not for limitation, the following binding conditions are provided for general guidance:

For antibody probes:

10-200 mM Tris, pH 6-8; usually 100 mM Tris pH 7.5
15-250 mM NaCl; usually 150 mM NaCl
0.01-0.5 percent, by volume, Tween 20
1 percent bovine serum albumin
4-37°C; usually 4° to 15°C

For polynucleotide probes:

3-10x SSC, pH 6-8; usually 5x SSC, pH 7.5
0-50 percent deionized formamide
1-10x Denhardt's solution
0-1 percent sodium dodecyl sulfate
10-200 µg/ml sheared denatured salmon sperm DNA
20-65°C, usually 37-45°C for polynucleotide probes
longer than 50 bp, usually 55-65°C for shorter
oligonulceotide probes

Additional examples of binding conditions for antibodies and polynucleotides are provided in several sources, including:

Maniatis et al., Molecular Cloning: A Laboratory Manual (1989), 2nd Ed., Cold Spring Harbor, N.Y. and Berger and Kimmel, Methods in Enzymology, Volume 152, Guide to Molecular Cloning Techniques (1987), Academic Press, Inc., San Diego, CA.; Young and Davis (1983) Proc. Natl. Acad. Sci. (U.S.A.) 80: 1194, which are incorporated herein by reference. When the probe is a receptor ligand, such as IL-2, β -interferon, or other polypeptide hormones, cytokines, or lymphokines, suitable binding conditions generally are those described in the art for performing the respective receptor-ligand binding assay.

Various examples of suitable binding conditions useful in immunoassays and immunohistochemistry are discussed,

for example, in Harlow and Lane, Antibodies: A Laboratory Manual, Cold Spring Harbor, New York (1988), which is incorporated herein by reference. In general, suitable binding conditions for immunological reactions include an aqueous binding buffer containing a salt (e.g., 5-500 mM NaCl or KCl), a buffer (e.g., Tris or phosphate buffer at pH 4-10), and optionally a nonionic detergent (e.g., Tween). In some embodiments, proteinase inhibitors or stabilizers may be included. The binding reactions are conducted for a suitable binding period, which, for antibody reactions, are typically at least about 1 to 5 minutes, preferably at least about 30 minutes to several hours, although typically less than about 24 hours, more preferably less than about a few hours or less. Binding reactions (including washes) are typically carried out a temperature range of about 0°C to about 45°C, preferably about 4°C to about 20-25°C.

Binding assays, which include in situ hybridization, in situ binding assays, and immunohistochemical staining, are usually performed by first incubating the sample with a blocking or prehybridization solution, followed by incubating the sample with probe under binding conditions for a suitable binding period, followed by washing or otherwise removing unbound probe, and finally by detecting the presence, quantity, and/or location of bound probe. The step of detecting bound probe can be accomplished by detecting label, if the probe is directly labeled, or by incubating the bound complex(es) with a second binding reagent (e.g., streptavidin) that is labeled and which binds to the probe, thus accomplishing indirect labeling of the probe.

Up-converting labels are attached to probe(s) or second binding reagents that specifically or preferentially bind to probe(s) by any of the various methodologies discussed herein. Additionally, up-converting phosphor particles can be encapsulated in microspheres and coated with a probe (e.g., a specific antigen or antibody) for use as a labeled probe in an immunodiagnostic assay or nucleic acid hybridization assay to detect an analyte in a sample, such as the presence of an

antibody, virus, or antigen in a blood serum sample, according to the method of Hari et al. (1990) Biotechniques 9: 342, which is incorporated herein by reference. Microencapsulation of phosphor can be accomplished in several ways known in the art, including coating the phosphor with a monomer solution and polymerizing the monomer to generate a polymer shell encasing the phosphor particle. Phosphor particles embedded in a polymer coating, such as a gel coating, can be functionalized (e.g., with amino groups) for covalent attachment to a binding component.

Similarly, up-converting phosphor particles can be coated with probe directly, either by surface adsorption, by multiple hydrogen bonding, by electrostatic interaction, by van der Waals binding, or by covalent linkage to a functional group on a functionalized inorganic phosphor particle (e.g., a vitroc ceramic phosphor), for example, by linking an amino acid side-chain amine or carboxylate group of a probe protein to a carboxylate or amine group, respectively, on a functionalized phosphor particle.

In certain embodiments, such as where steric and/or charge interference of a bulky up-converting phosphor particle inhibits binding of the linked binding reagent to a target, it is desirable to incorporate a molecular spacer between the phosphor particle and the binding reagent. For example, a derivatized microencapsulated phosphor or vitroc ceramic phosphor may be conjugated to a heterobifunctional reagent having a $-(CH_2)_n-$ spacer, where n is usually an integer from about 2 to about 50, between terminal functional groups. Similarly, phosphors may be directly derivatized with derivatizing agents (e.g., omega-functionalized silanes) having long intramolecular spacer chains, wherein a functional group reactive with a desired binding reagent is separated from the surface of the phosphor by a spacer of usually at least about 15 Å (i.e., the equivalent of about 10 $-CH_2-$ straight-chain groups). In some embodiments, labels are attached by spacer arms of various lengths to reduce potential

steric hindrance. Multiple layers of spacer arms may also be used (e.g., multiple layers of streptavidin-biotin linkages).

Multiple Analyte Detection

5 Since up-converting phosphors can be differentiated on the basis of the excitation and/or emission wavelength spectra, up-converting phosphors can be used to detect and discriminate multiple analyte targets, such as, for example, cell surface antigens or soluble macromolecules.

10 For example, streptavidin, avidin, or another linker macromolecule (e.g., antidigoxigenin antibody) are attached, respectively, to each of two different phosphors (for illustration, designated here as Phosphor#1 and Phosphor#2) which differ in their absorption and/or emission spectra so as
15 to facilitate discrimination of the two phosphors based on absorption and/or emission wavelengths; e.g., one phosphor may emit in the blue and the other may emit in the green. For example and not limitation, $\text{Na}(\text{Y}_{0.80}\text{Yb}_{0.18}\text{Er}_{0.02})\text{F}_4$ emits predominantly in the green, and $\text{Na}(\text{Y}_{0.73}\text{Yb}_{0.27}\text{Tm}_{0.001})\text{F}_4$ emits
20 predominantly in the blue, and thus these two phosphors may be discriminated on the basis of their phosphorescent emissions. Alternatively, two phosphors may produce essentially similar emission spectra but may have different excitation wavelengths which provide a basis for their discrimination in multiple
25 analyte detection. A first binding component (e.g., an antibody) that binds specifically to a first analyte species (e.g., a lymphocyte CD4 antigen) and incorporates biotinyl moieties which may be bound by streptavidin-Phosphor#1 conjugates can be used to quantitatively detect the presence
30 of a first analyte in a sample (e.g., a serum sample) by measuring phosphorescence of Phosphor#1 in analyte-binding component complexes. A second binding component (e.g., a probe polynucleotide) that binds specifically to a second analyte species (e.g., an HIV-1 sequence) and incorporates
35 digoxigenin moieties (e.g., 11-UTP-digoxigenin) which may be bound by antidigoxigenin-Phosphor#2 conjugates can be used to quantitatively detect the presence of a second analyte in the

sample by measuring phosphorescence of Phosphor#2 in analyte-binding component complexes. Thus, by simultaneously or contemporaneously detecting the presence of multiple phosphor reporters having differentiable signal characteristics, multiple analytes may be quantitatively detected in a single sample.

Sandwich Binding Assays

Up-converting phosphors labels can be used as reporters for sandwich binding assays (U.S. Patent 4,376,110, which is incorporated herein by reference). For example, a magnetic bead, such as a superparamagnetic immunobead or functionalized magnetizable polymer particle (Polysciences, Inc., Warrington, Pennsylvania), can serve as the solid substrate which has an immobilized first binding component (e.g., an antibody, a polynucleotide, or a lectin) that binds to a first epitope (i.e., a binding locus: an antigenic determinant, sugar moiety, chemical substituent, or nucleotide sequence) of an analyte. The analyte binds to the first binding component and also to a second binding component (e.g., an antibody, a lectin, or a polynucleotide) which binds to a second epitope of the analyte. Thus, the analyte bridges the two binding components to form a sandwich complex which is immobilized with respect to the solid substrate. The second binding component typically has an attached or incorporated label, such as a biotinyl group which can be bound to a streptavidin-coated up-converting phosphor. Alternatively, the second binding component can be linked directly to an up-converting phosphor, such as through a covalent linkage with a functionalized vitroc ceramic up-converting phosphor.

The sandwich complex comprises the first binding component, an analyte, and the second binding component, which is labeled, either directly or indirectly, with an up-converting reporter. The sandwich complex is thus immobilized on the solid substrate, although the solid substrate itself may be mobile (e.g., a superparamagnetic bead circulating in a sample slurry). The presence and amount of analyte(s) can be

quantitatively measured by detecting the presence of up-converting reporter in sandwich complexes.

For example, a solid substrate may have a plurality of distinct species of first binding component (e.g., an array of different oligopeptides affixed to a solid support). One or more of the species of first binding component may bind to a particular analyte (e.g., a muscarinic receptor) in an analyte solution that is in contact with the solid support. Binding of the analyte to one or more of the first binding component species may then be detected with a second binding component (e.g., an anti-muscarinic receptor antibody) labeled with an up-converting phosphor (either directly or through a biotinylated secondary antibody).

Solid substrates can be attached to a first binding component which can bind more than one distinct analyte (e.g., may be immunocrossreactive or polyspecific) and/or can be attached to multiple first binding component species which can bind multiple distinct analytes. Similarly, multiple second binding component species with binding specificities for particular analytes can be employed. When multiple second binding component species are employed, it is typically desirable to label each second binding component species with a unique up-converting label that can be distinguished on the basis of its absorption and/or emission properties.

It is possible to use different absorbers in combination with various emitters to produce a collection of phosphors having several differentiable combinations of excitation and emission spectra. For example but not limitation, six differentiable phosphors may be generated from two absorbers and three emitters. A first absorber, A_1 , has an excitation wavelength of λ_{A1} , a second absorber, A_2 has an excitation wavelength of λ_{A2} , a first emitter, E_1 , has an emission line at λ_{E1} , a second emitter, E_2 has an emission line at λ_{E2} , and a third emitter, E_3 , has an emission line at λ_{E3} . The six phosphors may be differentiated and the signal from each individually quantitated by illuminating the sample with an excitation wavelength λ_{A1} and detecting separately the

emitted radiation at λ_{E1} , λ_{E2} , and λ_{E3} , and separately illuminating the sample with λ_{A2} and detecting separately the emitted radiation at λ_{E1} , λ_{E2} , and λ_{E3} . Table II shows the various absorber:emitter combinations and their excitation and
5 emission wavelengths.

Table II

	<u>Absorber:Emitter Combination</u>	<u>Excitation λ</u>	<u>Emission λ</u>
10	A1:E1	λ_{A1}	λ_{E1}
	A1:E2	λ_{A1}	λ_{E2}
	A1:E3	λ_{A1}	λ_{E3}
	A2:E1	λ_{A2}	λ_{E1}
	A2:E2	λ_{A2}	λ_{E2}
15	A2:E3	λ_{A2}	λ_{E3}

Of course, additional absorber:emitter combinations are possible to provide more than six differentiable phosphor labels.

20 It is also possible to utilize solid substrates of different types which may be distinguished (e.g., by size, color, density, magnetic properties, shape, charge) so that a particular type of solid substrate is associated with a particular species of first binding component.

25 For example and not limitation, the following three brief examples are provided to explicate further possible applications of multiple analyte sandwich assay methods.

Substrate Differentiation

30 The following example describes the use of distinguishable substrate types to detect the presence of specific immunoglobulin idiotypes in a sample (e.g., a blood serum sample taken from a patient) which can provide diagnostic information about the immune status of a patient
35 (e.g., is a patient seroreactive with a particular antigen).

Large superparamagnetic beads are conjugated to an immunogenic Herpesvirus Type II envelope glycoprotein, medium-

sized superparamagnetic beads are conjugated to HIV gp120 glycoprotein, and small superparamagnetic beads are conjugated to an immunogenic cytomegalovirus envelope glycoprotein. A serum sample is taken from a patient and is incubated with a mixture of the superparamagnetic beads under binding conditions to permit specific binding of immunoglobulins in the sample with the three immobilized viral glycoprotein species. The superparamagnetic beads are separated from the sample to remove non-specifically bound immunoglobulin and incubated with up-converting phosphor particles coated with *Staphylococcus aureus* Protein A, which binds to IgG, under binding conditions. Superparamagnetic beads having specifically bound IgG are thus labeled with the phosphor-Protein A conjugate. Large, medium, and small superparamagnetic beads are then separately illuminated with phosphor excitation electromagnetic radiation and time-gated emitted phosphorescence is detected. Background attributable to non-specific binding, if any, is determined and subtracted using internal standard beads (bovine serum albumin coated superparamagnetic beads) and positive and negative control serum samples. The intensity of phosphorescence associated with the large, medium, and small beads provides a measure of the amount of antibodies in the sample which are reactive with the Herpesvirus Type II envelope glycoprotein, HIV gp120 glycoprotein, and cytomegalovirus envelope glycoprotein, respectively. This information can be used to determine whether an individual patient has been infected with the HIV-1, human CMV, and/or Herpes Simplex Type II viruses.

30 Phosphor Differentiation

The following example describes the use of differentiable up-converting phosphors to detect the presence and relative abundance of particular isoforms of human APP (amyloid precursor protein) in a serum or brain biopsy sample. Various isoforms of APP arise in the brain as a consequence of alternative exon usage and/or alternative proteolytic processing pathways. Thus, although all APP isoforms may

share a common, hypothetical epitope (X), a particular APP isoform may have a unique epitope (Y), while another APP isoform has a unique epitope (Z). It is possible that the relative abundance of a particular APP isoform in a sample may be of predictive value or may be pathognomonic for Alzheimer's Disease.

Superparamagnetic beads are conjugated to an antibody that binds specifically to a common APP epitope (X) shared by all isoforms. A specific antibody reactive with the unique Y epitope is labeled with Phosphor #1, which is excited by wavelength λ_1 and emits in a wavelength spectrum centered in the blue. A specific antibody reactive with the unique Z epitope is labeled with Phosphor #2, which is excited by a wavelength λ_2 and emits in a wavelength spectrum centered in the green. A sample containing APP isoforms is incubated with the superparamagnetic beads and labeled specific antibodies under binding conditions. The superparamagnetic beads are retrieved from the sample, either individually or in bulk. The beads are illuminated with wavelength λ_1 and blue light emission is detected and measured, and illuminated with λ_2 and green light emission is detected and measured. The intensity of λ_1 -induced blue emission is a measure of the APP isoform(s) having the Y epitope, while the intensity of the λ_2 -induced green emission is a measure of the APP isoform(s) having the Z epitope. If the emissions from two phosphors are readily distinguishable, λ_1 and λ_2 may be identical. The standardized relative intensities of the two phosphors provides a measure of the relative abundance of the APP isoform(s) containing the Y or Z epitopes.

Phosphor and Substrate Differentiation

The following example describes the use of differentiable up-converting phosphors in conjunction with distinguishable substrate types to detect the presence and relative abundance of particular T lymphocyte subpopulations in a blood sample taken from an individual. Although described here with reference to detecting T cell

subpopulations, analyte multiplexing (i.e., detecting and/or characterizing multiple analytes in a sample by using various solid substrate types and/or up-converting phosphor labels) is believed to be a generally applicable method.

5 Large superparamagnetic beads are conjugated to an anti-CD4 antibody, medium-sized superparamagnetic beads are conjugated to anti-CD8 antibody, and small superparamagnetic beads are conjugated to an anti-CD28 antibody. An antibody that specifically binds to the CD2 antigen is labeled with an
10 up-converting phosphor that has an excitation wavelength λ_1 and emits in the red. An antibody that specifically binds to the CD45R antigen is labeled with an up-converting phosphor that has an excitation wavelength λ_2 and emits in the green. An antibody that specifically binds to the CDw60 antigen is
15 labeled with an up-converting phosphor that has an excitation wavelength λ_3 and emits in the blue.

A blood (or serum, sputum, urine, feces, biopsy tissue, etc.) sample is taken from a patient and is incubated with a mixture of the superparamagnetic beads and phosphor-
20 labeled antibodies under binding conditions to permit specific binding of cells in the blood sample with the three bead-immobilized antibody species and the three phosphor-labeled antibody species. After antigen-antibody binding occurs, the superparamagnetic beads are segregated and examined, either
25 sequentially or simultaneously, by illumination with λ_1 , λ_2 , and λ_3 , and quantitative detection of red, green, and blue emissions, respectively. For example, the intensity of λ_1 -induced red light emission associated with the large beads is a rough measure of the amount of cells having both CD4 and CD2
30 surface antigens and/or the relative abundance of those surface antigens (e.g., there may be very few CD4⁺ cells that have CD2, but those few cells may have a large amount of CD2 antigen, and hence a large CD2 phosphorescent signal). Similarly, the intensity of λ_2 -induced green light associated
35 with the large beads is a rough measure of the amount of cells having both CD4 and CD45R surface antigens and/or the relative abundance of those surface antigens in a sample.

In this manner, an analyte sample, such as a blood sample, can be "fingerprinted" for the presence and relative distribution(s) (e.g., cosegregation and/or correlation) of various analyte species. Such an analyte fingerprint may be used for providing diagnostic or therapeutic information, for example, as to measuring a patient's immune status or measuring response to chemotherapy directed against a particular blood cell subset. Similar analyte fingerprints can be used to type pathogenic organisms and viruses, as well as to order polynucleotide sequences for gene mapping and/or sequencing.

Superparamagnetic beads which can be differentiated based on size, shape, color, or density can be magnetically trapped individually and scanned with appropriate excitation illumination(s) and phosphor emission(s) characteristic of particular analytes detected. For example, a unitary detector can simultaneously or contemporaneously trap the superparamagnetic bead from a suspension, determine the bead type (size, shape, and/or color), and scan for presence and abundance of particular phosphors (by illuminating with excitation wavelength(s) and detecting emitted wavelengths).

By performing binding assays under dilute conditions wherein an average of one analyte or less (e.g., lymphocyte) is bound per microbead, it is possible to type cells individually (e.g., determine the abundance of CD45R on each individual CD4⁺ cell) and thus generate more precise lymphocyte subpopulation definitions.

Biotinylated magnetic beads can also be used to monitor the kinetics of binding streptavidin to phosphor particles and/or to segregate or purify streptavidin-coated up-converting phosphor particles from a reaction. Thus, streptavidin and up-converting phosphor particles are mixed in a reaction vessel under binding conditions for forming streptavidin-coated phosphor particles. After a suitable binding period, unbound streptavidin may be removed (e.g., by centrifugation wherein phosphor particles are collected as the pellet, unbound streptavidin in the supernatant is decanted,

and the pellet is resuspended), biotinylated magnetic beads are added to the remaining phosphor suspension in binding conditions, and streptavidin-coated phosphor particles are recovered bound to the biotinylated magnetic beads.

5

Photophysical Catalysis by Up-Converting Phosphors

Other applications of the invention employ phosphors as a photophysical catalyst linked to a probe, where the radiation emitted by the phosphor is used, typically in conjunction with a dye molecule, to produce localized intense electromagnetic radiation in an area adjacent to the probe for various purposes other than detection (e.g., cytotoxicity, ionization of chemical species, mutagenesis, etc.). For example, an antibody that specifically binds to a cell surface antigen, such as a CD8 antigen on a CD8⁺ lymphocyte, may be used as a probe linked to a up-converting phosphor to localize the phosphor to CD8⁺ lymphocytes. A sample containing CD8⁺ lymphocytes can be incubated with the anti-CD8⁺ probe-phosphor conjugate and irradiated with an excitation wavelength (e.g., from an infrared laser diode), resulting in emission of up-shifted photons (i.e., higher frequency electromagnetic radiation) in the vicinity of CD8⁺ lymphocytes to which the anti-CD8⁺ probe-phosphor conjugate has bound. The emitted radiation may be of a wavelength that is directly mutagenic and/or cytotoxic (e.g., ultraviolet radiation that can lead to formation of thymine dimers, 760-765 nm light is also believed to produce chromosomal damage) or may be of a wavelength that can cause a photolytic decomposition of a chemical present in the environment, leading to local formation of reactive species that may damage adjacent cells (e.g., photodecomposition of buckminsterfullerene, C₆₀, to C₅₈ and C₂, may produce free radicals that may cause lipid peroxidation of cell membranes).

Since phosphor-emitted radiation is isotropic, it is generally desirable to physically separate targets (e.g., CD8⁺ lymphocytes) from non-targets (e.g., CD8⁻ lymphocytes) prior to excitation irradiation, so that undesirable damage to non-

targets by isotropic emission(s) (i.e., "secondary damage") is avoided. Physical separation may be accomplished by various means, including but not limited to: (1) performing excitation irradiation on a dilute suspension of target and non-target cells, wherein the mean distance separating individual cells is sufficient to reduce secondary damage to non-targets, and (2) employing hydrodynamic focusing to pass cells (both targets and non-targets) single file through an illumination zone (e.g., as in a fluorescence-activated cell sorter or the like). Thus, an up-converting phosphor linked to an anti-CD8⁺ antibody can be used to selectively damage CD8⁺ lymphocytes in a lymphocyte sample, where (1) the phosphor emits at a wavelength that is either directly cytotoxic and/or (2) the phosphor emits at a wavelength that produces reactive chemical species by photocatalysis of a compound present in the sample (e.g., a sample can be doped with buckminsterfullerene).

Instead of using the emitted radiation directly for photocatalytic action on tissue or tumors, an excited form of oxygen, so called singlet excited oxygen ($O_2^1\Delta_g$) can be generated by energy transfer from a dye sensitizer to dissolved molecular oxygen. This scheme makes use of the tissue penetrating power of near-infrared radiation (red and ultrared region light, including 970 nm) which reaches the inorganic up-converting phosphor. Two of the infrared photons are converted either into a red, green, or blue photon depending on the absorption spectrum of the sensitizer dye. The dye is excited by the up-converted radiation into a triplet state which transfers its energy to a dissolved molecular oxygen molecule to yield an excited (singlet) oxygen molecule. The cytotoxic activity of singlet oxygen is well documented in photodynamic therapy and other biomedical applications (see, Wagnieres et al. (19-21 January 1990) Future Directions and Applications of Photodynamic Therapy, pp. 249, SPIE Institutes for Advanced Optical Technologies, Society of Photo-Optical Instrumentation Engineers, Box 10, Bellingham, Washington 98277; Pelegrin et al. (1991) Cancer 67: 2529; Wagnieres et al. (24-25 May 1991) Future Directions

and Applications of Photodynamic Therapy, pp. 219; Folli et al. (17 December 1991) Fluoresceine Clinique 4; Braichotte et al. (May 1991) ENT-Clinic, Lausanne, Switzerland).

In this application the up-converting phosphor is
5 mixed or laced with a sensitizing dye such as methylene blue, rose bengal or phthalocyanine derivatives, such as Zn-phthalocyanine. In the first and third case a red-emitting phosphor is used, whereas for rose bengal a green-emitting phosphor is best suited. The phthalocyanine derivatives are
10 ideally suited for this purpose because of their total insolubility in aqueous or biological solutions. These dyes therefore stay in close proximity to the emitters so that the specificity of the cell surface-reporter/probe/dye complex becomes the limiting factor. In this case, specialized
15 combinations of reporter/probe/dye formulations preferably in the 0.1 to 0.3-micron size range must be synthesized in order to enable efficient energy transfer: first, up-converted radiation is absorbed by the dye as completely as possible; and second, the dye excited energy (triplet state) is
20 transferred to dissolved molecular oxygen. Both processes are very efficient if the absorption spectrum of the sensitizer dye is matched to the up-converted radiation.

This scheme presents a step beyond the traditional photodynamic therapy methods in that the red light can be used
25 both for tracking and diagnostic as well as for therapeutic purposes after up-converting thus necessitating only one (infrared) light source at about 1000 nm. A further advantage is the greater range within biological samples of the infrared radiation compared to other known photodynamic therapy
30 excitation schemes (750-850 nm).

For embodiments employing up-converting phosphors as photophysical catalysts, it is generally desirable that: (1) the wavelength(s) of the excitation radiation do not produce significant photocatalysis of the substrate compound, (2) the
35 wavelength(s) of the excitation radiation are not directly cytotoxic or mutagenic, and (3) the emitted radiation is directly cytotoxic and/or is of an appropriate wavelength to

produce a biologically effective amount of photodecomposition of a substrate compound (e.g., buckminsterfullerene, psoralen, compounds containing azide substituents or other photoactivated groups). Alternatively, histidine side chains of polypeptides can be oxidized by light in the presence of dye sensitizers, such as methylene blue or rose bengal (Proteins, Structures and Molecular Principles, (1984) Creighton (ed.), W.H. Freeman and Company, New York; Introduction to Protein Structure, (1991), C. Branden and J. Tooze, Garland Publishing, New York, NY, which are incorporated herein by reference). Thus, for example, up-converting phosphors linked to anti-CD8 antibodies can be used as photophysical catalysts to produce selective, localized damage to CD8⁺ lymphocytes. In accordance with the invention, essentially any antibody can be linked to an appropriate up-converting phosphor, either directly or by conjugation to protein A which may then bind the immunoglobulin. Thus, the up-converting photophysical catalysts of the invention may be used to target essentially any desired antigen or cell type that can be distinguished by the presence of an identified antigen.

Up-Converting Organic Dyes

Similar to the up-converting inorganic phosphor reporters we propose to use "molecular" labels whose fluorescence will be detected by optoelectronic means. Infrared or red light is exciting the probe-reporter complex bound to a target, after which light is emitted at shorter wavelengths with respect to the illuminating source. This up-converted light is free of scattered light from the source or autofluorescence by virtue of its higher energy. Furthermore, autofluorescence is greatly reduced by virtue of the excitation in the infrared or red spectral range. The light source is a pump laser whose pump pulses are short in order to achieve high powers and low energy in order to enable non-linear optical processes in the dye. The goal is to excite the second excited singlet state (S_2) in a dye with a ps pulse

from a tunable dye laser using two red or infrared photons. After pumping the S_2 state the dye relaxes within a few ps to the fluorescing state (S_1) which can be detected by optoelectronic means. The goal of reaching the S_2 state using two photons enables one to take advantage of the increasing two-photon cross sections as one approaches the S_2 state using two-photon absorption. The non-resonant two-photon absorption cross sections are on the order of 10^{-49} to 10^{-50} cm^4s , whereas the cross sections corresponding to S_2 absorption are larger by two to three orders of magnitude. A few specific examples will be mentioned: in general cyanines, xanthenes, rhodamines, acridines and oxazines are well suited for this purpose. Blue dyes can also be used, but the excitation wavelength will be in the red. Rhodamine can be excited at 650 to 700 nm using two photons, and fluorescence is expected around 555 nm. Many IR dyes such as IR-140, IR-132 and IR-125 can be excited at 1060 nm using two photons of the Nd:YAG fundamental, and fluorescence is expected in the 850 to 950 nm range. An example of a blue dye is BBQ excited at 480 nm to reach the S_2 state at 240 nm, and fluorescence is expected at 390 nm. Many of these dyes are only slightly soluble in aqueous solution and are either polar in nature (cyanines) or have polar substituents. Depending on the nature of the probe, no or only minimal attachment chemistry needs to be undertaken because of the abundance of functional groups on the dye chromophore. Several companies sell entire lines of dyes: examples are KODAK, Exciton and Lambda Physik. The scientific foundations of two-photon laser excitation in organic dye molecules have been treated in a few experimental papers: A. Penzkofer and W. Leupacher, Optical and Quantum Electronics 19 (1987), 327-349; C. H. Chen and M. P. McCann, Optics Commun. 63 (1987), 335; J. P. Hermann and J. Ducuing, Optics Commun. 6 (1972), 101; B. Foucault and J. P. Hermann, Optics Commun. 15 (1975), 412; Shichun Li and C. Y. She, Optica Acta 29 (1982), 281-287; D. J. Bradley, M. H. R. Hutchinson and H. Koetser, Proc. R. Soc. Lond. A 329 (1972), 105-119.

Resonant Multiphoton Ionization

At very high laser intensities the up-converting organic dyes are induced to absorb an additional exciting photon in the field of focussed laser radiation. At those
5 high laser intensities the fluorescence is suppressed in favor of absorption of an additional photon. This process usually brings the organic dye molecules above the ionization limit in solution and they stabilize by emitting an electron into the solvent shell. The result of this three-photon interaction is
10 a molecular ion and an attached or solvated electron. When this charge separation is taking place in an electric field, the charges drift and generate a voltage that can be detected in an extremely sensitive manner. This amounts to the measurement of the transient conductivity in the solvent
15 system and is usually more sensitive than light detection. The disadvantage of this method is that it necessitates electrodes that sense the moving charges. In that sense it is not as non-invasive a method as light detection. On the other hand it bypasses the conversion of light into a photoelectric
20 signal which represents an enormous advantage. Every optical system has a restricted viewing angle that reduces efficiency, whereas photoionization "senses" always close to 100% of the charges generated. Effectively, the non-linear interaction of the laser field converts every excited organic dye molecule
25 into an electric pulse at sufficiently high field intensities that can be routinely achieved using commercial laser sources. Specific examples are the excitation of Rhodamine around 650 to 700 nm, or BBQ excitation around 480 nm. Organic dyes absorbing in the red have to absorb two additional photons
30 after being excited into S_2 thus making the whole process a four-photon excitation process, which is slower than a three-photon non-linear process. There may, however, be circumstances where such a four-photon process is desirable.

35 Detection Apparatus

Detection and quantitation of inorganic up-converting phosphor(s) is generally accomplished by: (1)

illuminating a sample suspected of containing up-converting phosphors with electromagnetic radiation at an excitation wavelength, and (2) detecting phosphorescent radiation at one or more emission wavelength band(s).

5 Illumination of the sample is produced by exposing the sample to electromagnetic radiation produced by at least one excitation source. Various excitation sources may be used, including infrared laser diodes and incandescent filaments, as well as other suitable sources. Optical filters
10 which have high transmissibility in the excitation wavelength range(s) and low transmissibility in one or more undesirable wavelength band(s) can be employed to filter out undesirable wavelengths from the source illumination. Undesirable wavelength ranges generally include those wavelengths that
15 produce detectable sample autofluorescence and/or are within about 25-100 nm of excitation maxima wavelengths and thus are potential sources of background noise from scattered excitation illumination. Excitation illumination may also be multiplexed and/or collimated; for example, beams of various
20 discrete frequencies from multiple coherent sources (e.g., lasers) can be collimated and multiplexed using an array of dichroic mirrors. In this way, samples containing multiple phosphor species having different excitation wavelength bands can be illuminated at their excitation frequencies
25 simultaneously. Illumination may be continuous or pulsed, or may combine continuous wave (CW) and pulsed illumination where multiple illumination beams are multiplexed (e.g., a pulsed beam is multiplexed with a CW beam), permitting signal discrimination between phosphorescence induced by the CW
30 source and phosphorescence induced by the pulsed source, thus allowing the discrimination of multiple phosphor species having similar emission spectra but different excitation spectra. For example but not limitation, commercially available gallium arsenide laser diodes can be used as an
35 illumination source for providing near-infrared light.

The ability to use infrared excitation for stimulating up-converting phosphors provides several

advantages. First, inexpensive IR and near-IR diode lasers can be used for sustained high-intensity excitation illumination, particularly in IR wavelength bands which are not absorbed by water. This level of high-intensity

5 illumination would not be suitable for use with conventional labels, such as ordinary fluorescent dyes (e.g., FITC), since high-intensity UV or visible radiation produces extensive photobleaching of the label and, potentially, damage to the sample. The ability to use higher illumination intensities
10 without photobleaching or sample damage translates into larger potential signals, and hence more sensitive assays.

The compatibility of up-converting labels with the use of diode lasers as illumination sources provide other distinct advantages over lamp sources and most other laser
15 sources. First, diode laser intensity can be modulated directly through modulation of the drive current. This allows modulation of the light for time-gated or phase-sensitive detection techniques, which afford sensitivity enhancement without the use of an additional modulator. Modulators
20 require high-voltage circuitry and expensive crystals, adding both cost and additional size to apparatus. The laser diode or light-emitting diode may be pulsed through direct current modulation. Second, laser illumination sources provide illumination that is exceptionally monochromatic and can be
25 tightly focused on very small spot sizes, which provides advantages in signal-to-noise ratio and sensitivity due to reduced background light outside of the desired excitation spectral region and illuminated volume. A diode laser affords these significant advantages without the additional expense
30 and size of other conventional or laser sources.

Detection and quantitation of phosphorescent radiation from excited up-converting phosphors can be accomplished by a variety of means. Various means of detecting phosphorescent emission(s) can be employed,
35 including but not limited to: photomultiplier devices, avalanche photodiode, charge-coupled devices (CCD), CID devices, photographic film emulsion, photochemical reactions

yielding detectable products, and visual observation (e.g., fluorescent light microscopy). If the reporters are organic dyes, resonant multiphoton ionization can be sensed using electrostatic position-sensitive detectors. Detection can
5 employ time-gated and/or frequency-gated light collection for rejection of residual background noise. Time-gated detection is generally desirable, as it provides a method for recording long-lived emission(s) after termination of illumination; thus, signal(s) attributable to phosphorescence or delayed
10 fluorescence of up-converting phosphor is recorded, while short-lived autofluorescence and scattered illumination light, if any, is rejected. Time-gated detection can be produced either by specified periodic mechanical blocking by a rotating blade (i.e., mechanical chopper) or through electronic means
15 wherein prompt signals (i.e., occurring within about 0.1 to 0.3 μ s of termination of illumination) are rejected (e.g., an electronic-controlled, solid-state optical shutter such as Pockell's or Kerr cells). Up-converting phosphors and up-converting delayed fluorescent dyes typically have emission
20 lifetimes of approximately a few milliseconds (perhaps as much as 10 ms, but typically on the order of 1 ms), whereas background noise usually decays within about 100 ns. Therefore, when using a pulsed excitation source, it is generally desirable to use time-gated detection to reject
25 prompt signals.

Since up-converting phosphors are not subject to photobleaching, very weak emitted phosphor signals can be collected and integrated over very long detection times (continuous illumination or multiple pulsed illumination) to
30 increase sensitivity of detection. Such time integration can be electronic or chemical (e.g., photographic film). When non-infrared photographic film is used as a means for detecting weak emitted signals, up-converting reporters provide the advantage as compared to down-converting phosphors
35 that the excitation source(s) typically provide illumination in a wavelength range (e.g., infrared and near infrared) that does not produce significant exposure of the film (i.e., is

similar to a darkroom safelight). Thus, up-converting phosphors can be used as convenient ultrasensitive labels for immunohistochemical staining and/or in situ hybridization in conjunction with fluorescence microscopy using an infrared source (e.g., a infrared laser diode) and photographic film (e.g., Kodak Ektachrome) for signal and image detection of visible range luminescence (with or without an infrared-blocking filter).

10 Instrumentation Overview

Fig. 1 is an optical and electronic block diagram illustrating representative apparatus 10 for performing diagnostics on a sample 15 according to the present invention. The invention may be carried out with one or a plurality of reporters. For purposes of illustration, the apparatus shows a system wherein two diagnostics are performed on a single sample in which two phosphor reporters are used. The first reporter has an excitation band centered at λ_1 and an emission band centered at λ_1' while the second reporter has respective excitation and emission bands centered at λ_2 and λ_2' . Since the reporters of the present invention rely on multiphoton excitation, wavelengths λ_1 and λ_2 are longer than wavelengths λ_1' and λ_2' . The former are typically in the near infrared and the latter in the visible.

A pair of light sources 20(1) and 20(2), which may be laser diodes or light-emitting diodes (LEDs), provide light at the desired excitation wavelengths, while respective detectors 22(1) and 22(2), which may be photodiodes, detect light at the desired emission wavelengths. The emitted radiation is related to the incident flux by a power law, so efficiency can be maximized by having the incident beam sharply focused on the sample. To this end, light from the two sources is combined to a single path by a suitable combination element 25, is focused to a small region by a lens or other focusing mechanism 27, and encounters the sample. Light emitted by the phosphor reporters is collected by a lens 30, and components in the two emission bands are separated by

a suitable separation element 32 and directed to the respective detectors.

There are a number of possible regimes for driving the laser diodes and detecting the emitted light in the different wavelength bands. This is shown generically as a control electronics block 35 communicating with the laser diodes and detectors. The particular timing and other characteristics of the control electronics will be described below in connection with specific embodiments.

There may be a plurality of reporters having distinct emission bands but a common excitation band. In such a case, the system would include multiple detectors for a single laser diode. Similarly, there may be a plurality of reporters having distinct excitation bands but a common emission band. In such a case, the system would include multiple laser diodes for a single detector, and would use time multiplexing techniques or the like to separate the wavelengths.

Light from the two sources is shown as being combined so as to be focused at a single location by a common focusing mechanism. This is not necessary, even if it is desired to illuminate the same region of the sample. Similarly, the collection need not be via a single collection mechanism. If it is necessary to preserve all the light, the combination and separation elements can include a wavelength division multiplexer and a demultiplexer using dichroic filters. If loss can be tolerated, 50% beam splitters and filters can be used.

The schematic shows the light passing through the sample and being detected in line. As a general matter, the emission from the phosphor reporters is generally isotropic, and it may be preferred to collect light at an angle from the direction of the incident light to avoid background from the excitation source. However, since the excitation and the emission bands are widely separated, such background is unlikely to be an issue in most cases. Rather, other considerations may dictate other geometries. For example, it

may be desired to detect light traveling back along the path of the incident radiation so that certain elements in the optical train are shared between the excitation and the detection paths.

5 A typical type of instrument with shared elements is a microscope where the objective is used to focus the excitation radiation on the sample and collect the emitted radiation. A potentially advantageous variation on such a configuration makes use of the phenomenon of optical trapping. 10 In a situation where the reporter is bound to a small bead, it may be possible to trap the bead in the region near the beam focus. The same source, or a different source, can be used to excite the reporter. The use of an infrared diode laser to trap small particles is described in Sato et al., "Optical 15 trapping of small particles using a $1.3\mu\text{m}$ compact InGaAsP laser," Optics Letters, Vol. 16, No. 5 (March 1, 1991), incorporated herein by reference.

Specific Detection Techniques

20 As outlined above, multichannel detection uses optical devices such as filters or dichroic beam splitters where the emission bands of the phosphor reporters are sufficiently separated. Similarly, it was pointed out that multiple reporters having a common emission band could be 25 detected using electronic techniques. These electronic techniques will be described below in connection with multiple sources. However, the techniques will be first described in the context of a single channel. The techniques are useful in this context since there are sources of background that are in 30 the same wavelength range as the signal sought to be measured.

Fig. 2A shows an apparatus for implementing phase sensitive detection in the context of a single channel. Corresponding reference numerals are used for elements corresponding to those in earlier described figures. In this 35 context, control electronics 35 comprises a waveform generator 37 and a frequency mixer 40. Waveform generator 37 drives laser diode 20(1) at a frequency f_1 , and provides a signal at

f_1 to the frequency mixer. The frequency mixer also receives the signal from detector 22(1) and a phase control input signal. This circuitry provides additional background discrimination because the background has a much shorter lifetime than the signal sought to be measured (nanoseconds or microseconds compared to milliseconds). This causes the signal and background to have different phases (although they are both modulated at the characteristic frequency of the waveform generator). For a discussion of the lifetime-dependent phase shift, see Demtröder, Laser Spectroscopy, Springer-Verlag, New York, 1988, pp. 557-559, incorporated herein by reference). The phase input signal is controlled to maximize the signal and discriminate against the background. This background discrimination differs from that typical for phase sensitive detection where the signal is modulated and the background is not. Discrimination against unmodulated background is also beneficial here, leading to two types of discrimination.

Because the signal relies on two-photon excitation, it is possible to use two modulated laser diodes and to detect the signal at the sum or difference of the modulation frequencies. Fig. 2B shows such an arrangement where first and second laser diodes 20(1) and 20(1)' (emitting at the same wavelength λ_1 , or possibly different wavelengths) are modulated by signals from waveform generators 37a and 37b operating at respective frequencies f_a and f_b . The waveform generator output signals are communicated to a first frequency mixer 42, and a signal at $f_a \pm f_b$ is communicated to a second frequency mixer 45. The signal from detector 22(1) and a phase input signal are also communicated to frequency mixer 45.

Fig. 3 shows apparatus for performing gated detection. Since the background is shorter-lived than the signal, delaying the detection allows improved discrimination. To this end, the laser diode is driven by a pulse generator 50, a delayed output of which is used to enable a gated integrator or other gated analyzer 55.

Fig. 4 shows an apparatus for performing diagnostics on a sample using first and second, reporters having excitation bands centered at λ_1 and λ_2 , and having overlapping emission bands near λ_3 . The sample is irradiated by light from laser diodes 20(1) and 20(2) as discussed above in connection with Fig. 1. First and second waveform generators 37(1) and 37(2) drive the laser diodes at respective frequencies f_1 and f_2 , and further provide signals at f_1 and f_2 to respective frequency mixers 60(1) and 60(2). The signal from detector 22(3) is communicated to both frequency mixers, which also receive respective phase input signals. Thus, frequency mixer 60(1) provides an output signal corresponding to the amount of emitted light modulated at frequency f_1 , which provides a measure of the presence of the first reporter in the sample. Similarly, frequency mixer 60(2) provides an output signal corresponding to the amount of emitted light modulated at frequency f_2 , which provides a measure of the presence of the second reporter in the sample.

The use of two different wavelengths was discussed above in the context of two reporters having different excitation bands. However, the discussion is germane to a single reporter situation as well. Since the excitation is a two-photon process, there is no requirement that the two photons have the same energy. Rather, it is only necessary that the total energy of the two photons fall within the excitation band. Thus, since it is relatively straightforward and inexpensive to provide different wavelengths with laser diodes, there are more possible combinations, i.e., more possible choices of total excitation energy. This allows more latitude in the choice of rare earth ions for up-converters since the excitation steps need not rely on energy transfer coincidences involving a single photon energy. Further, it may be possible to achieve direct stepwise excitation of the emitting ion (the erbium ion in the example outlined above) without using energy transfer from another absorbing ion (the ytterbium ion in the example) while taking advantage of resonant enhancement of intermediate levels. Additionally,

the use of different wavelengths for a single reporter can provide additional options for excitation-dependent multiplexing and background discrimination techniques.

Multiple wavelength excitation of a single phosphor may occur in a number of ways, as shown in Figs. 5A through 5C. Two lasers may cause stepwise excitation of a single ion, as shown in Fig. 5A. A first laser stimulates excitation from level 1 to level 2, and a second laser stimulates excitation from level 2 to level 3, at which level emission occurs. Single ion excitation can also occur using energy transfer as shown in Fig. 5B. In this case, a first laser stimulates excitation from level 1 to level 2, energy transfer occurs from level 2 to level 3, and a second laser stimulates excitation from level 3 to level 4. In a variation of the latter process, levels 1 and 2 can be in a first ion (i.e., a sensitizer ion) and levels 3 and 4 in a second ion (i.e., activator ion) as shown in Fig. 5C.

In a stepwise excitation scheme shown in Fig. 5A, energy transfer is not required, and thus information on the polarization of the excitation lasers may be preserved and cause polarization of the emitted radiation. In this case, depolarization of the light may allow for enhanced discrimination between signal and background noise.

For the multi-ion multi-laser excitation scheme shown in Figure 5C, there may be several phosphors that share a common excitation wavelength. In this case, discrimination between different phosphors may be performed on the basis of different emission wavelengths and/or through time-gated, frequency-modulated, and/or phase-sensitive detection utilizing modulation of the excitation wavelength(s).

Specific Instrument Embodiments

Fig. 6 is a schematic view showing the optical train of a particular embodiment of apparatus for carrying out the present invention on a sample using a hand-held probe. This embodiment takes the form of a miniaturized instrument comprising a housing 75 (shown in phantom), a hand-held probe

80, with a fiber optic connecting cable 82. The optical and electronics components are located within the housing. For purposes of illustration, the optical components of a 3-channel system are shown. The sample may contain up to three
5 reporters having distinct emission bands, for example, in the blue, green, and red portions of the visible spectrum. It is also assumed that the reporters have distinct excitation bands in the near infrared.

The output beams from three laser diodes 85a-c are
10 communicated through graded index (GRIN) lenses 87a-c, focused onto the ends of respective fiber segments 88a-c and coupled into a single fiber 90 by a directional coupler 92 or other suitable device. The light emerging from the end of fiber 90 is collimated by a GRIN lens 95, passes through a dichroic
15 beam splitter 97, and is refocused by a GRIN lens 100 onto the end of fiber optic cable 82. The beam splitter is assumed to pass the infrared radiation from the laser diodes but reflect visible light.

Hand-held probe 80 includes a handpiece 102, an
20 internal GRIN lens 105, and a frustoconical alignment tip 110. The light emerging from fiber 82 is focused by GRIN lens 105 at a focus point 115 that is slightly beyond alignment tip 110. The alignment tip is brought into proximity with the test tube holding the sample so that focus point 115 is in the
25 sample. It is assumed that the test tube is transmissive to the laser radiation.

A portion of the light emanating from the region of focus point 115 in the sample is collected by GRIN lens 105, focused into fiber 82, collimated by GRIN lens 100, and
30 reflected at dichroic beam splitter 97. This light may contain wavelengths in up to the three emission bands. Optical filters 120a-c direct the particular components to respective photodetectors 125a-c. A particular filter arrangement is shown where each filter reflects light in a
35 respective emission band, but other arrangements would be used if, for example, one or more of the filters were bandpass filters for the emission bands.

The control electronics are not shown, but could incorporate the time-multiplexed or heterodyne techniques discussed above. Such techniques would be necessary, for example, if the emission bands were not distinct.

5 Fig. 7A is a schematic of an embodiment of the invention in which a charge coupled device (CCD) imaging array 150 is used as a detector in combination with a two dimensional array 152 of peptides or other biologically active species deposited on a glass or plastic substrate. The CCD
10 array has a number of individually addressable photosensitive detector elements 155 with an overlying passivation layer 157 while the peptide array has a number of individual binding sites 160. The probe containing the phosphor would be reaction specific to one or more of the elements in this
15 peptide array and would therefore become physically attached to those elements and only those elements. The peptide array is shown as having a one-to-one geometric relation to the imaging array in which one pixel corresponds to each element in the peptide array. However, it is also possible to have
20 larger peptide elements that cover a group of detector elements should such be necessary.

Various of the techniques described above can be used to enable the detector array to distinguish the emissions of the phosphor from the infrared laser stimulation.

25 First, it is possible to use a phosphor that responds to IR stimulation beyond the sensitivity range of the detector array. An example of such a phosphor would be Gadolinium oxysulfide : 10% Erbium. This phosphor is stimulated by 1.5-micron radiation and emits at 960 nm and
30 520 nm. The detector array is insensitive to 1.5-micron radiation but is sensitive to the up-converted radiation.

Further, since the phosphor emission is relatively slow in rise and fall time it could be time resolved from a pulsed laser stimulation source by the CCD detector array.
35 The decay time for the upconversion process is a variable dependent on the particular emitting transition and the phosphor host; however, it is normally in the range 500 μ s

seconds to 10 ms. This is very slow compared to the laser excitation pulse and the capability of the detector array.

The techniques for fabricating the CCD array are well-known since CCD imaging arrays have been commercially available for many years. A variety of such devices can be obtained from David Sarnoff Research Center, Princeton, NJ.

The techniques for fabricating the peptide array are described in a paper by Fodor et al., "Light-Directed, Spatially Addressable Parallel Chemical Synthesis, " Science, Vol. 251, pp. 767-773 (February 15, 1991), incorporated herein by reference. The particular array described contains 1024 discrete elements in a 1.28 cm x 1.28 cm area.

The embodiment of Fig. 7A shows the peptide array in intimate contact with the CCD array. Indeed it may be possible to deposit the peptides directly on the passivation layer without a separate substrate. However, there may be situations where spatially separated arrays are preferred Fig. 7B shows an embodiment where the peptide array and the CCD array are separated. An array of lenses 165 collect the light from respective binding sites and focus it on respective detector elements. This arrangement facilitates the use of filters to the extent that other techniques for rejecting the excitation radiation are not used.

Optical trapping may be used to transiently immobilize a sample particle for determination of the presence or absence of phosphor on the particle. Conveniently, the wavelength range used to trap sample particles may be essentially identical to an excitation wavelength range for the up-converting phosphor(s) selected, so that optical trapping and excitation illumination is performed with the same source. Fig. 8 shows a block diagram of an apparatus used for single-beam gradient force trapping of small particles.

35 Fluorescence-activated Cell Sorting

The up-converting phosphors described herein can be used as phosphorescent labels in fluorescent cell sorting by

flow cytometry. Unlike conventional fluorescent dyes, up-converting phosphors possess the distinct advantage of not requiring excitation illumination in wavelength ranges (e.g., UV) that damage genetic material and cells. Typically, up-converting phosphor labels are attached to a binding reagent, such as an antibody, that binds with high affinity and specificity to a cell surface protein present on a subset of cells in a population of cells in suspension. The phosphor-labeled binding component is contacted with the cell suspension under binding conditions, so that cells having the cell surface protein bind to the labeled binding reagent, whereas cells lacking the cell surface protein do not substantially bind to the labeled binding reagent. The suspended cells are passed across a sample detector under conditions wherein only about one individual cell is present in a sample detection zone at a time. A source, typically an IR laser, illuminates each cell and a detector, typically a photomultiplier or photodiode, detects emitted radiation. The detector controls gating of the cell in the detection zone into one of a plurality of sample collection regions on the basis of the signal(s) detected. A general description of FACS apparatus and methods is provided in U.S. Patents 4,172,227; 4,347,935; 4,661,913; 4,667,830; 5,093,234; 5,094,940; and 5,144,224, incorporated herein by reference. It is preferred that up-converting phosphors used as labels for FACS methods have excitation range(s) (and preferably also emission range(s)) which do not damage cells or genetic material; generally, radiation in the far red, and infrared ranges are preferred for excitation. It is believed that radiation in the range of 200 nm to 400 nm should be avoided, where possible, and the wavelength range 760 nm to 765 nm may be avoided in applications where maintenance of viable cells is desired.

35 Additional Variations

In environments where absorption of the up-converted phosphor radiation is high, the phosphor microparticles are

coated with a fluorescent dye or combination of dyes, in selected proportions, which absorb at the up-converted frequency and subsequently re-radiate at other wavelengths. Because the single-photon absorption cross-sections for these
5 fluors are typically very high, only a thin layer is required for complete absorption of the phosphor emission. This coat particle may then be encapsulated and coated in a suitable antigen or antibody receptor (e.g. microparticle). An example of this layering is depicted schematically in Fig. 9. There
10 exists a wide variety of fluorescent dyes with strong absorption transitions in the visible, and their emission covers the visible range and extends into the infrared. Most have fluorescent efficiencies of 10% or more. In this manner, the emission wavelengths may be custom-tailored to pass
15 through the particle's environment, and optical interference filters may again used to distinguish between excitation and emission wavelengths. If a relatively large wavelength "window" in the test medium exists, then the variety of emission wavelengths which may be coated on a single type of
20 phosphor is limited only by the number of available dyes and dye combinations. Discrimination between various reporters is then readily carried out using the spectroscopic and multiplexing techniques described herein. Thus, the number of probe/reporter "fingerprints" which may be devised and used in
25 a heterogenous mixture of multiple targets is virtually unlimited.

The principles described above may also be adapted to driving species-specific photocatalytic and photochemical reactions. In addition to spectroscopic selection, the long
30 emission decay times of the phosphors permit relatively slow reactions or series of reactions to take place within the emission following photoexposure. This is especially useful when the phosphor-[catalyst or reactant] conjugate enters an environment through which the excitation wavelength cannot
35 penetrate. This slow release also increases the probability that more targets will interact with the particle.

The unique decay rates of phosphor particles allow dynamic studies as well. In a system where continuous exposure to the excitation source is not possible, or is invasive and thereby undesirable, pulsed excitation followed by delayed fluorescence detection is necessary. After the phosphor reporter has been photoexcited, the subsequent emission from the phosphor or phosphor/dye conjugate particle lasts typically about a millisecond. In a dynamic environment, such as a static or flowing system with moving targets, the particle will emit a characteristically decaying intensity of light as it travels relative to the excitation/detection apparatus. Combined with imaging optics appropriate to the scale of the system and the velocities within the system, a CCD photoelectric sensor array will be used to detect the particle or particles movement across the array's field of view. The delayed emission of the phosphors, which is a well-characterized function of time, makes possible the dynamic tracking of individual particle's positions, directions and velocities, and optionally calculation of particle size, density, and hydrodynamic conformation. As a particle moves, it exposes more elements of the array, but with every-decreasing intensity. The more elements it exposes over a certain fraction of its decay time, the faster it is moving. Therefore, the integrated intensity pattern of a particle's emission "track" collected by the array is directly related to the velocity of the particle. The particles may be refreshed again at any time by the pulsed or chopped CW excitation source. Fig. 10 illustrates this scheme. Although only a depiction of "side-on" excitation and detection is shown, both side-on and end-on detection and excitation arrangements, or combinations, are possible. Reduction of the CCD array intensity information by computer analysis will allow near-real time tracking of the particles in a dynamically evolving or living systems. Data analysis and reduction performed by the computer would include a convolution of the intrinsic decay of the phosphor emission, the number of pixels illuminated and their signal level, the

orientation of the decaying signal on the array, and the intensity contributions from a blur circle from particles moving in and out of the focal plane of the array. In an end-on flow detection arrangement, the size of the blur circle would relate directly to how quickly the particle moves out of focus, thereby allowing the velocity of the particle to be determined. One possible application would be monitoring the chemistry and kinetics in a reaction column, alternatively, the application of this method to flow cytometry may permit the resolution of cells on the basis of hydrodynamic properties (size, shape, density). The method may also be useful for in vivo diagnostic applications (e.g., blood perfusion rate).

Up-converting phosphor labels may also be used to sense the temperature in the region at which the up-converting phosphor label is bound. Up-converting phosphor temperature measurement methods are described in Berthou H and Jorgensen CK (October, 1990) Optics Lett. 15(19): 1100, incorporated herein by reference.

Although the present invention has been described in some detail by way of illustration for purposes of clarity of understanding, it will be apparent that certain changes and modifications may be practiced within the scope of the claims.

The broad scope of this invention is best understood with reference to the following examples, which are not intended to limit the invention in any manner.

EXPERIMENTAL EXAMPLES

Validation of Up-Converting Inorganic Phosphors as Reporters

Up-converting phosphor particles comprising sodium yttrium fluoride doped with ytterbium-erbium were milled to submicron size, fractionated by particle size, and coated with polycarboxylic acid. $\text{Na}(\text{Y}_{0.80}\text{Yb}_{0.18}\text{Er}_{0.02})\text{F}_4$ was chosen for its high efficiency upon excitation in the range 940 to 960 nm. A Nd:Yag pumped dye laser/IR dye combination was used to generate 8-ns to 10-ns duration pulses in the above frequency range.

The laser pulses were used to illuminate a suspension of milled phosphor particles in liquid and attached to glass slides in situ. The suspension luminescence observed at right angles was monitored using a collection lens, a spatial filter in order to filter out scattered excitation light to the maximum possible extent, and a photomultiplier, vacuum photodiode, or simple solid state photodiode (depending on the light level observed).

The luminescent signal level was determined as a function of solution pH (range: 6-8), grain size, particle loading ($\mu\text{g}/\text{cm}^3$), and the nature of stabilizing anionic surfactant. Signals were recorded both as a time integral from a boxcar integrator and from a long RC time constant or as a transient signal using a transient digitizer in order to delineate the luminescence lifetime under particular experimental conditions. In situ signals were also measured by laser scanning microscopy. Fig. 11 is a fluorescence scan of the phosphor emission spectrum incident to excitation with a laser source at a wavelength maximum of 977.2 nm; emission maximum is about 541.0 nm. Fig. 12 is an excitation scan of the phosphor excitation spectrum, with emission collection window set at 541.0 nm; excitation maximum for the phosphor at the 541.0 nm, emission wavelength is approximately about 977 nm. Fig. 13 is a time-decay measurement of the phosphor luminescence at 541.0 nm after termination of excitation illumination; maximal phosphorescence appears at approximately 400 μs with a gradual decay to a lower, stable level of phosphorescence at about 1000 μs . Fig. 14 shows the phosphor emission intensity as a function of excitation illumination intensity; phosphorescence intensity increases with excitation intensity up to almost about 1000 W/cm^3 .

Phosphorescence efficiencies of submicron $\text{Na}(\text{Y}_{0.8}\text{Yb}_{0.12}\text{Er}_{0.08})\text{F}_4$ particles were measured. A Ti:sapphire laser was used as an excitation source and a spectrophotometer and photomultiplier was used as a detection system. Two types of measurement were performed. The first was a direct measurement in which the absolute emission per particle for

phosphor suspensions was measured in emission bands at 540 nm and 660 nm. The calibrated cross-sections are shown in Fig. 15, and size-dependence is shown graphically in Fig. 16. This corresponded to a phosphorescence cross-section of approximately $1 \times 10^{-16} \text{ cm}^2$ for $0.3 \mu\text{m}$ particles with excitation light at 975 nm and an intensity of approximately 20 W/cm^2 . The emission efficiency of dry phosphor powder of about $25 \mu\text{m}$ was also measured. On the basis of known values for the absorption cross-section of Yb^{+3} in crystalline hosts (Lacovara et al. (1991) Op. Lett. 16: 1089, incorporated herein by reference) and the measured dependence of the phosphorescence emission on particle size, a phosphorescence cross-section of approximately $1 \times 10^{-15} \text{ cm}^2$ was found. The difference between these two measurements may be due to a difference in phosphorescence efficiency between dry phosphor and aqueous suspensions, or due to absorption of multiply scattered photons in the dry phosphor. On the basis of either of these cross-section estimates, the cross-section is sufficiently large to allow detection of single submicron phosphor particles at moderate laser intensities. At laser intensities of roughly 10 W/cm^2 , the phosphorescence scales as the laser intensity to the 1.5 power.

Phosphor Particle Performance: Sensitivity of Detection

A series of Terasaki plates containing serial dilutions of monodisperse $0.3 \mu\text{m}$ up-converting phosphor particles consisting of $(\text{Y}_{0.86}\text{Yb}_{0.08}\text{Er}_{0.06})_2\text{O}_2\text{S}$ were tested for up-conversion fluorescence under IR diode laser illumination in a prototype instrument.

The phosphor particles were prepared by settling in DMSO and were serially diluted into a 0.1% aqueous gum arabic solution. This appeared to completely eliminate any water dispersion problems. The serial dilutions used are listed in Table III.

TABLE III

Label	Phosphor Loading (ng/well)	Phosphor Loading (particles/well)	Equivalent Detection Sensitivity (M)
10^0	1700±90	23,600,000±1,200,000	4×10^{-12}
10^{-1}	170±9	2,360,000±120,000	4×10^{-13}
10^{-2}	17±0.9	236,000±12,000	4×10^{-14}
10^{-3}	1.7±0.09	23,600±1,200	4×10^{-15}
10^{-4}	0.170±0.009	2,360±120	4×10^{-16}
10^{-5}	0.017±0.0009	236±12	4×10^{-17}
10^{-6}	0.0017±0.00009	23.6±1.2	4×10^{-18}

The stock DMSO dispersion had a phosphor density of 1.70±0.09 mg/mL (at 95% confidence limits), determined gravimetrically by evaporating 4-1 mL samples. This translates to 23.6×10^9 particles/mL (assuming an average particle size of 0.3 μ m and particle density of 5.3 g/mL). The residue after evaporating the samples over the weekend at 110-120°C was noticeably yellow, but did phosphoresce when tested with an IR diode laser.

Visual green light emanated from all serial dilutions down to 10^{-3} (i.e., 1.7 μ g/mL or 23.6×10^6 particles/mL) in a 1 mL polypropylene microfuge tube using a hand-held diode laser in a dark room. The 10^{-1} and 10^{-2} dilutions were visibly cloudy. Either 1 μ l of each serial dilution, or 0.1 μ l of the next higher dilution, were pipetted into a well on the Terasaki plate. It was found that 1 μ l fills the bottom of the well and 0.1 μ l spreads along the edge of the well, but does not cover the entire surface. Because of the statistical and pipetting problems associated with small volumes with low particle concentrations, 2 to 4 replicates were prepared of each dilution.

The well of a Terasaki plate holds a 10 μ l sample volume. Assuming all the phosphor particles contained in this volume adhere to the bottom of the sample well, we can estimate an equivalent detection sensitivity (Table III). It

Goat anti-mouse IgG antibody (Ab) was conjugated (by adsorption) the DMSO fractionated phosphor particles. This was done by mixing 200 μL of the Ab solution (in 0.1M Tris-HCl, pH 7.2) with 100 μL of the phosphor suspension in DMSO.

5 Several different Ab concentrations were tried in the range of 0.025 to 1 $\mu\text{g}/\mu\text{L}$. A concentration of 0.25 $\mu\text{g}/\mu\text{L}$ appeared to result in the most efficient coating (i.e., maximum Ab utilization with a minimum of clumping of the phosphor particles). The phosphors were equilibrated overnight at room
10 temperature with the Ab in this DMSO/Tris solution with gentle agitation. The resulting phosphor-Ab conjugates were centrifuged from this solution and resuspended in a 3 $\mu\text{g}/\text{mL}$ BSA solution in PBS for post-coating. The resulting BSA/PSA resuspension was used directly for the assay.

15 The degree of Ab adsorption to the phosphors, and residual Ab activity, was determined by titrating the phosphor-bound Ab with a fluorescein isothiocyanate (FITC) conjugated-mouse IgG. The resulting FITC-labeled phosphors were passed through a Cyteron Absolute flow cytometer, which
20 was also capable of measuring the relative size of the particles. Two distinct size subpopulations were observed with about 65% of the counted particles appearing as small, presumably monodisperse particles, and 35% being significantly larger, presumably aggregates. Only 60% of the smaller
25 subpopulation appeared to have significant quantities of active Ab (determined by FITC fluorescence). Of the purported aggregates, about 90% appeared to contain active Ab (by FITC fluorescence). This suggests that less than 40% of the phosphor-Ab conjugates were of an appropriate size (nominal
30 0.3 μm) and exhibited anti-mouse IgG activity. A similar fraction of phosphor-Ab conjugates (31%) were active but carried a significantly larger phosphor reporter.

The PMT signal (amps) was recorded at each plate position and numerically integrated over the width of the
35 sample well (approximately 4000 μm). The average signals (with 95% confidence limits) are:

Average of Positive Samples = $1.30 \times 10^{-4} \pm 1.25 \times 10^{-4} \mu\text{a-m}$

Average of Negative Controls = $4.20 \times 10^{-6} \pm 6.82 \times 10^{-6}$ $\mu\text{a-m}$
The positive samples and negative controls are statistically
different at the 99.9% confidence level. The positive samples
emit on average 30.0 ± 29.7 times more light than the negative
5 controls.

Linkage of Phosphors to Biological Macromolecules

In order to delineate further the parameters for up-
converting phosphors as biochemical reporters, biological
10 linkers were attached to phosphor particles. Sodium yttrium
fluoride-ytterbium/erbium phosphor particles were coated with
streptavidin. The excitation and emission spectral properties
of the phosphor alone and the phosphor coated with
streptavidin were measured (Figs. 17A, 17B, 18A, and 18B) and
15 both the uncoated and streptavidin-coated phosphors were
almost identical in their absorption and emission properties,
indicating that the attachment of macromolecular linkers
(e.g., proteins) have little if any effect on the
phosphorescent properties of the up-converting phosphor. The
20 streptavidin-coated phosphors were then specifically bound to
biotinylated magnetic beads, demonstrating the applicability
of linker-conjugated inorganic phosphors as reporters in
biochemical assays, such as immunoassays,
immunohistochemistry, nucleic acid hybridizations, and other
25 assays. Magnetic bead technology allows for the easy
separation of biotin-bound streptavidin-coated phosphor from a
solution, and is particularly well-suited for sandwich assays
wherein the magnetic bead is the solid substrate.

Advantageously, streptavidin-biotin chemistry is
30 widely used in a variety of biological assays, for which up-
converting phosphor reporters are suited. Fig. 20 shows
schematically, for example and not limitation, one embodiment
of an immunoassay for detecting an analyte in a solution by
binding the analyte (e.g., an antigen target) to a
35 biotinylated antibody, wherein the analyte forms a sandwich
complex immobilized on a solid substrate (e.g., a magnetic
bead) by linking a first binding component bound directly to

the solid substrate to a second binding component (e.g., the biotinylated antibody); a streptavidin-coated up-converting phosphor then binds specifically to the biotinylated antibody in the sandwich and serves to report formation of the sandwich complex on the solid substrate (which is a measure of the analyte concentration). When the solid substrate is a magnetic bead, it is readily removed from the sample solution by magnetic separation and the amount of phosphor attached to the bead(s) in sandwich complex(es) are determined by measuring specific up-converting phosphorescence. Thus, sandwich complex phosphorescence provides a quantitative measure of analyte concentration.

Biotinylated polynucleotides are also conveniently used as hybridization probes, which can be bound by streptavidin-coated up-converting phosphors to report hybrid formation.

Background Phosphorescence in Biological Samples

Background signals were determined in two biological samples for determination of potential background in immunoassays. Sputum and urine were used as samples in the same apparatus as used for the phosphorescence sensitivity measurements (supra). No background levels were found above the system noise levels set by the photomultiplier dark current. This noise level allows detection of signals from on the order of a few hundred particles/cm³. This is close to a single particle in the detection volume of the system.

A photomultiplier is a preferred choice for a detector for high sensitivity measurements of up-converting phosphors since photomultipliers can be selected to produce high quantum efficiency at the up-converted (i.e., emitted) wavelengths and virtually no response in the range of the longer excitation wavelengths.

Detection of Cell Antigens with Phosphor-Labeled Antibodies

Streptavidin is attached to the up-converting phosphor particles as described, supra. The mouse lymphoma

cell line, EL-4, is probed with a hamster anti-CD3 antibody which specifically binds to the 30 kD cell surface EL-4 CD3 T lymphocyte differentiation antigen. The primary hamster antibody is then specifically bound by a biotinylated goat-
5 antihamster secondary antibody. The biotinylated secondary antibody is then detected with the streptavidin-phosphor conjugate. This type of multiple antibody attachment and labeling is termed antibody layering.

Addition of multiple layers (e.g., binding the
10 primary hamster Ab with a goat-antihamster Ab, followed by binding with a biotinylated rabbit-antigoat Ab) are used to increase the distance separating the phosphor from the target. The layering effect on signal intensity and target detection specificity is calibrated and optimized for the individual
15 application by performing layer antibody layering from one layer (primary antibody is biotinylated) to at least five layers and ascertaining the optimal number of layers for detecting CD3 on EL-4 cells.

Fig. 21 schematically portrays simultaneous
20 detection of two EL-4 cell surface antigens using phosphors which can be distinguished on the basis of excitation and/or emission spectra. Detection of both antigens in the scheme shown in Fig. 21 uses a biotinylated terminal antibody which is conjugated to streptavidin-coated phosphor (#1 or #2) prior
25 to incubation with the Ab-layered sample. Thus, the phosphor-antibody specificity is retained through the unusually strong (K_D approx. $1 \times 10^{15} \text{ M}^{-1}$) non-covalent bond between streptavidin and biotin which is pre-formed before incubation with the primary antibody-bound sample. Quantitation of each
30 antigen is accomplished by detecting the distinct signal(s) attributable to each individual phosphor species. Phosphorescent signals can be distinguished on the basis of excitation spectrum, emission spectrum, fluorescence decay time, or a combination of these or other properties.

35 Fig. 22 shows a schematic of an apparatus for phase-sensitive detection, which affords additional background discrimination. The pulse or frequency mixer is set to pass

the signal and discriminate against the background following frequency calibration for maximum background rejection.

Covalent Conjugation of Upconverting Phosphor Label to Avidin

5 An upconverting yttrium-ytterbium-erbium ($Y_{0.86}Yb_{0.08}Er_{0.06}$) oxysulfide (O_2S) phosphor was linked to avidin by the following procedure:

10 Monodisperse upconverting phosphor particles were silanized with thiopropyltriethoxysilane (Huls) following the procedure detailed by Arkles (in: Silicone Compounds: Register and Review, Hills America, pgs. 59-75, 1991). This consisted of adding thiopropyltriethoxysilane (2g) and 95% aq. ethanol (100mL) to a 500 mL Erlenmeyer flask and stirred for 2 minutes. Approximately 8 mL of the 65 mg/mL phosphor
15 suspension in DMSO was then added to the mixture. This suspension was stirred for an additional 2 minutes, then transferred to centrifuge tubes and centrifuged to separate the phosphor particles. The pellets were washed twice with 95% aq. ethanol centrifuging each time. The resulting
20 particles were collected and dried overnight under vacuum at approximately 30°C. A quantity (127mg) of dry silanized phosphors were resuspended in 1.5 mL of DMSO (phosphor stock).

 A solution containing 1.19 mg of avidin (Pierce) in 1.0mL of borate buffer (954mg sodium borate decahydrate and
25 17.7 mL of 0.1 N NCl in 50 mL of deionized water, pH 8.3) was prepared (Avidin stock). Another solution containing 1.7 mg of N-succinimidyl(4-iodoacetyl) aminobenzoate (Pierce Chemical) in 1.2 mL of DMSO was prepared (SIAB stock). A quantity (10 μ L) of the SIAB stock was added to the 1.0mL of
30 Avidin stock and stirred at room temperature 30 min to allow the N-hydroxysuccimide ester of the SIAB to react with primary amines on the avidin (Avidin-SIAB stock).

 A 20mL scintillation vial was prepared containing 10mL of borate buffer (pH 8.3). The following additions were
35 then made to this vial: 21.6 μ L of the avidin-SIAB stock solution followed by 1.5mL of the phosphor stock. This reaction mixture was stirred at room temperature in the dark

overnight to allow the SIAB activated avidin to react with the thiol groups present on the silanized phosphor surface and resulting in the covalent linkage of avidin to the phosphor particles.

5 After the overnight incubation 1.0mL of the reaction mixture was centrifuged (1 min at 10,000g) and the supernatant removed. The pellet was resuspended in 1.0 mL of phosphate buffered saline (pH 7.2, Pierce) and centrifuged again to wash any unconjugated protein from the phosphors. This washing
10 process was repeated. The washed pellet was resuspended in 1.0mL of phosphate buffered saline and used directly in diagnostic assays as described below.

Measurement Apparatus

15 A modified SLM Aminco 48000 Fluorimeter was used to measure the fluorescence spectrum from the phosphor samples. The modifications to this device consisted of adding a laser diode (David Sarnoff CD-299R-FA #13) which was input to the fluorimeter through port 3. The laser diode emits at $\lambda =$
20 985.1 nm. Spectral data provided by the David Sarnoff Research Center also shows a small peak at 980.2 nm. This peak has 15% the intensity of the peak at 985 nm.

A 5.08 cm focal length lens was used to collimate the diode laser beam. The power of the IR laser light was
25 measured as 6.1 mW at the cuvette location with a drive current of 75 mA. The beam was not focused at the center of the cuvette. This is true for the standard visible light from the fluorimeter excitation monochromator as well. The laser diode beam is diverging as it enters the cuvette holder and is
30 approximately 4 mm (H) x 2 mm (V) by the time it reaches the center of the cell, neglecting the changes in refractive index of the cell wall and the liquid.

Light emitted is scanned with a monochromator and detected by a photomultiplying tube (PMT) 90° from the
35 direction of the excitation light. The detection limits for the modified SLM Aminco 48000 were determined by serial dilution to be $4 \times 10^{-16}M$ (240,000 phosphor particles per mL)

in PBS. Phosphor emission peaks in the spectrum were seen at wavelengths of $406 \pm 2 \text{ nm}$, $434 \pm 2 \text{ nm}$, $522 \pm 2 \text{ nm}$, and $548 \pm 2 \text{ nm}$. The largest peak was at 548 nm. The intensity of the 548 nm peak was used to discriminate samples.

5

Linkage of Avidin-Phosphor Conjugate to Cell Surface Marker

A lymphoblastoid cell line (Human Genetic Mutant Cell Repository #GM07092) was cultured in RPMI 1640 media containing 15% heat inactivated fetal calf serum. A suspension of cells (10^7 cells) was centrifuged and resuspended in an equal volume of phosphate buffered saline (PBS) pH 7.4. Cells were washed two times in PBS and resuspended to a final concentration of 5×10^6 cells/ml. These cells were then incubated with a mouse IgG1 monoclonal antibody to human β_2 -microglobulin, a Class I histocompatibility antigen in polystyrene centrifuge tubes. The cells were immunoprecipitated for 30 minutes at 4°C with an antibody concentration of $10 \mu\text{g/ml}$. The cells were harvested by centrifugation, washed twice in PBS, resuspended in PBS and then aliquoted ($250 \mu\text{L}$) into six fresh centrifuge tubes. Four of these samples received biotinylated goat anti-mouse IgG, while the remaining two received FITC-labelled goat anti-mouse IgG. These immunoprecipitations were performed at 4°C for 30 minutes in volume of $400 \mu\text{L}$ with a final second antibody concentration of $20 \mu\text{g/ml}$. The cells were harvested and washed in PBS as above but were resuspended in $50 \mu\text{L}$ of blocking buffer (0.2% purified casein in PBS, Tropix, Bedford, MA). The cell-antibody complexes were blocked in this solution for 30 minutes at room temperature and then transferred to fresh tubes.

A pre-blocked suspension ($40 \mu\text{L}$) of either avidin-Phosphor conjugate, avidin-FITC, avidin, or unconjugated Phosphor was added to four of the cell samples conjugated with the biotinylated anti-mouse IgG (H&L). In addition, an equal amount of pre-blocked avidin-Phosphor or unconjugated Phosphor was added to the remaining two cell samples immunoprecipitated with the non-biotinylated FITC-labelled anti-mouse IgG (H&L).

The avidin reporter conjugates or negative controls were pre-blocked as follows. Avidin-Phosphor and Phosphor alone was diluted in blocking buffer by adding 10 μL of a 6.7 mg/ml suspension to a final volume of 100 μL . Avidin-FITC and the
5 avidin alone controls were also diluted in blocking buffer by adding 27 μL of 2.5 mg/ml solution to a final volume of 100 μL . These reagents were blocked at room temperature for 3 hours with intermittent resuspension and then added to 50 μL of cells labelled with biotinylated or non-biotinylated second
10 antibody. The avidin-biotin reactions were performed at room temperature for 30 minutes with occasional resuspension. The reactions were stopped by harvesting the cells by centrifugation and washing twice in blocking buffer. The samples were resuspended in 100 μL of blocking buffer and
15 allowed to settle for 4-5 minutes. Slides for imaging were prepared by pipetting 5 μL of settled cells from the bottom of the tube. Cells were imaged by confocal laser microscopy under appropriate conditions to observe cell surface FITC and upconverting phosphor signals. The observations are
20 summarized in Table IV.

The remainder of the samples were used to resuspend paramagnetic, polystyrene beads bound with sheep anti-mouse IgG. For each of the six samples, 3×10^7 beads were pre-washed with blocking buffer for 1 hour at room temperature in
25 Eppendorf tubes. The buffer was removed by aspiration while the tubes were in a magnetic rack. The magnetic beads with anti-mouse IgG were allowed to bind to the antibody labelled cells for 1 hour at room temperature with intermittent resuspension. The magnetic beads were then collected on a
30 magnetic rack, washed four times in blocking buffer, resuspended in 100 μL blocking buffer, transferred to a fresh tube, and up-converting phosphorescence was measured on the fluorimeter.

To scan for phosphor emission, the emission
35 monochromator bandwidth was set to 8nm and the spectra were scanned from 500 to 700nm with a step size of 2nm. Samples were also measured for FITC signal by exciting the samples

with 37 μM at $\lambda = 490\text{nm}$ with a 2 nm bandwidth. Since the excitation wavelength (490 nm) and the emission wavelength (514 nm) are very close for FITC, higher resolution was required to get separable signals than with phosphor labelling. The intensity of the 490nm signal was 240 $\mu\text{W}/\text{cm}^2$ at the center of the well. FITC emission spectra were scanned at 0.5nm increments from 450nm to 750nm with a 2 nm bandwidth on the emission monochromator. Sample 1 is the positive control and clearly yielded the highest emission signal. Sample 2 indicates that any nonspecific adsorption of the phosphors to the sample is limited and is readily discriminated from signal attributable to avidin-conjugated phosphor and showing that avidin linked phosphors can specifically bind only when they are conjugated with the probe, in this example through the biotin-avidin linkage. Sample 3 is the negative control which contains no phosphors, only avidin. Sample 4 shows FITC-conjugated avidin. Although FITC signals were observed on the cell surface by laser microscopy, the signals were below the level of detection on the fluorimeter for measurement of FITC, and since there was no phosphor in the sample there was no significant phosphor signal. Samples 5 and 6 show that FITC-conjugated primary antibodies can be detected and that the presence of phosphor or avidin-phosphor does not significantly disrupt binding of the primary antibody to its target antigen.

Table IV

Tube	Type of goat anti-mouse IgG	Avidin Conjugate	Cell Surface Phosphor Signal	Cell Surface FITC Signal
1	biotinylated	Avidin-Phosphor	+	-
2	biotinylated	Phosphor	-	-
3	biotinylated	Avidin	-	-
4	biotinylated	Avidin-FITC	-	+
5	FITC labelled	Avidin-Phosphor	-	+
6	FITC labelled	Phosphor	-	+

Linkage of Avidin-Phosphor Conjugate to DNA

Plasmid DNA (25 μ g) was nick translated in the presence of 20 mM dGTP, 20 mM dCTP, 20 mM biotin-14 dATP, 13 mM dTTP, and 7 mM digoxigenin-11 dUTP and purified by ethanol precipitation. The average size of the biotinylated, digoxigenin labelled fragments was estimated to be between 200-300 nucleotides as estimated by gel electrophoresis. Approximately 20 μ g DNA was immunoprecipitated for 1 hour at 22°C with 10 μ g/ml mouse monoclonal anti-digoxigenin IgG1 solution (PBS) in a 200 μ L volume. An equivalent reaction containing no DNA was also prepared. Each of the two samples were then aliquoted (50 μ L) into three fresh Eppendorf tubes.

The avidin-conjugates were blocked for 1 hour at room temperature by diluting 500 μ g of an avidin-phosphor suspension, unconjugated phosphor suspension, or avidin solution in 300 μ L of blocking buffer. For each of the samples (summarized below in Table V) 50 μ L of the anti-digoxigenin conjugates was added to 150 μ L of pre-blocked avidin-conjugates or avidin and were incubated for 30 minutes at room temperature.

Unbound avidin-conjugates were removed by resuspending 3×10^7 paramagnetic beads linked with sheep anti-mouse IgG (pre-blocked in blocking buffer). After incubation for 30 minutes at room temperature with intermittent resuspension, the beads were separated on a magnetic rack and washed 4 to 6 times in PBS. The antibody-DNA bound beads were then measured on the fluorimeter.

The samples were scanned from 500 to 700 nm with a bandwidth of 8 nm and step size of 2 nm. Each PMT value reported (Table V) represents an average over 5 scans. Sample 1 is expected to provide the highest PMT signal since biotinylated DNA is present and can bind to the avidin-linked phosphors. Sample 2 indicates the level of nonspecific adsorption of the phosphors to the sample which is found to be insignificant since the PMT signal is observed to be the same as that of the negative control (sample 4) which contains no phosphors. Sample 3 is another control and shows that the

avidin-linked phosphors do not bind to the paramagnetic beads in the absence of DNA. Samples 5 and 6 show results of FITC-labeled avidin used to validate assay.

Table V

Upconverting Phosphor Nucleic Acid Diagnostic Assay Results

Sample	DNA	Reporter	PMT Signal (V @546nm)	PMT Signal (V @514nm)
1	DNA labeled with digoxigenin and biotin	Avidin linked Phosphor	6.1297	2.4788
2	DNA labeled with digoxigenin and biotin	Silanized Phosphor	1.0528	4.4022
3	No DNA	Avidin linked Phosphor	1.6302	3.5779
4	DNA labelled with digoxigenin and biotin	Avidin	0.8505	2.8067
5	DNA labelled with digoxigenin and biotin	FITC-Avidin	1.0484	8.4394
6	No DNA	FITC-Avidin	1.0899	3.5779

Phosphor Downconversion Evaluation

A sample of the $(Y_{0.86}Yb_{0.08}Er_{0.06})_2O_3$ phosphors were scanned for the presence of a downconverted signal. This was accomplished by exciting a sample of the monodisperse phosphors described above ($4 \times 10^{-12}M$ in DMSO) with 1.3 mW of monochromatic light at 350 nm with a 16 nm bandwidth for the excitation source. Detection was accomplished by scanning this sample from 350 to 800 nm with a monochromator bandwidth of 8 nm. Scanning was performed in 2 nm increments. No downconversion was observed. Moreover, no downconversion was

seen at the excitation wavelengths cited by Tanke et al. (U.S. Patent 5,043,265). Thus, the upconverting phosphors tested are unlike those reported in Tanke et al.

5

HOMOGENEOUS ASSAYS

The multiphoton activation process characteristic of upconverting phosphors can be exploited to produce assays that require no sample washing steps. Such diagnostic assays that do not require the removal of unbound phosphor labels from the sample are herein termed homogeneous assays, and can also be termed pseudohomogeneous assays.

Homogeneous Assay Example 1

One embodiment of a homogeneous assay consists of the use of an upconverting phosphor label linked to an appropriate probe (e.g., an antibody or DNA). The phosphor-labeled probe specifically binds to a target (e.g., antigen or nucleic acid) that is linked to a capturing surface. A suitable capture surface can be the tip of a light carrying optical fiber (Fig. 23) or the bottom surface of a sample container (Fig. 24). Upon incubation of the target-labelled capture surface with the phosphor-labelled probe, phosphor particles will accumulate at the capture surface as a function of the amount of target present on the capturing surface. The target may be linked directly to the capturing surface or may be immobilized by interaction with a binding agent (e.g., specific antibody reactive with target, polynucleotide that binds target) that is itself linked to the capturing surface (such as in a sandwich immunoassay, for example).

Detection of the phosphor bound to the capture surface is effected using an excitation light that is focused from a low intensity beam of large cross-section to a high intensity beam of small cross-section with the focal point of the beam being at or very near the capture surface. Focusing of the excitation light is accomplished by transmission through optical elements that have a very small focal

distance, such that the beam diverges, becoming less intense, within a short distance of the capture surface.

Since the intensity of the light emitted from the upconverting phosphor labels is proportional to the excitation light intensity raised to a power of two or greater, phosphors near the focal point of the excitation source will emit significantly more light than those remaining in suspension in the sample away from the capture surface. Therefore, binding of upconverting phosphor linked probes to the capture surface will yield an increase in emitted light intensity measured from the sample as a whole or as measured from a control sample in which phosphors do not bind to the capture surface. Emitted light intensity may be plotted as a function of target concentration using for standardization (calibration) a series of samples containing predetermined concentrations of target. The emitted light intensity from a test sample (unknown concentration of target) can be compared to the standard curve thus generated to determine the concentration of target.

Examples of suitable homogeneous assay formats include, but are not limited to, immunodiagnostic sandwich assays and antigen and/or antibody surface competition assays.

Homogeneous Assay Example 2

Another embodiment allows for the accumulation of upconverting phosphor linked probes at the detection surface by the application of centrifugal or gravitational settling. In this embodiment an upconverting phosphor is linked to multiple probes. All the probes must bind to the same target, although said binding can be accomplished at different locations (e.g., as antibody probes may target different epitopes on a single antigen). The multiprobe phosphor can then be used to effect the aggregation of targets in solution or suspension in the sample. This aggregation will result in the formation of a large insoluble phosphor-probe-target complex that precipitates from solution or suspension (Fig. 25). The aggregated complex containing phosphors accumulates at a detection surface while nonaggregated material remains in

solution or suspension. Detection is accomplished as described in the above example using a sharply converging excitation beam.

Although the present invention has been described in
5 some detail by way of illustration for purposes of clarity of understanding, it will be apparent that certain changes and modifications may be practiced within the scope of the claims.

CLAIMS

1. A method for detecting an analyte in a sample, comprising the steps of:

5 attaching an up-converting label to a probe forming a labeled probe;

contacting a sample containing a target analyte with the labeled probe under binding conditions forming labeled probe-target complexes;

10 removing unbound labeled probe from the labeled probe-target complexes in the sample; and

detecting labeled probe-target complexes by illuminating with a label excitation wavelength and detecting light emission of at least one label emission wavelength.

15 2. A method according to Claim 1, wherein said up-converting label is an up-converting inorganic phosphor comprising at least one rare earth element in a host material.

20 3. A method according to Claim 2, wherein the up-converting inorganic phosphor comprises sodium yttrium fluoride ytterbium erbium or yttrium ytterbium erbium oxysulfide.

4. A method according to Claim 1, wherein the probe is selected from the group consisting of: antibodies,
25 polynucleotides, polypeptide hormones, streptavidin, *Staphylococcus aureus* Protein A, lectins, and antigens.

5. A method according to Claim 1, wherein the probe is attached to the label by covalent or noncovalent binding.

30

6. A method according to Claim 5, wherein the probe is streptavidin or avidin.

7. A method according to Claim 1, wherein the step of
35 removing unbound labeled probe from the labeled probe-target complexes in the sample is performed by washing the sample

with an aqueous solution to remove soluble unbound labeled probe.

8. A method according to Claim 7, wherein the labeled probe-
5 target complexes are immobilized on a solid support.
9. A method according to Claim 8, wherein the labeled probe-
target complexes are bound sandwich complexes.
10. A method according to Claim 1, wherein the target analyte
is selected from the group consisting of: polynucleotides,
polypeptides, viruses, microorganisms, haptens, mammalian
cells, steroid hormones, glycoproteins, lipoproteins,
biotinylated magnetic beads, and pharmaceuticals.
15
11. A method according to Claim 1, wherein the step of
illuminating with a label excitation wavelength is performed
with an infrared laser diode or light-emitting diode.
- 20 12. A method according to Claim 11, wherein the infrared
laser diode or light-emitting diode emits pulsed illumination.
13. A method according to Claim 12, wherein the infrared
laser diode or light-emitting diode is pulsed through direct
25 current modulation.
14. A method according to Claim 12, wherein the step of
detecting light emission of at least one label emission
wavelength is performed by time-gated or lock-in detection.
30
15. A method according to Claim 11, wherein the step of
detecting light emission is performed with phase-sensitive
detection.
- 35 16. A method according to Claim 11, wherein the laser diode
or light-emitting diode has peak emissions in the range of
960-980 nm and at approximately 1500 nm.

17. A method according to Claim 1, wherein said step of detecting light emission is performed with a photomultiplier, a CCD, a CID, or photographic film emulsion.

5 18. A method According to Claim 1, wherein the target analyte is immobilized in a histological tissue section or a solid support.

19. A method for detecting an analyte in a sample, comprising
10 the steps of:

contacting a sample containing a target analyte with a probe under binding conditions forming probe-target complexes;

15 attaching an up-converting label to the probe-target complexes forming labeled probe-target complexes;

removing unbound up-converting label from the labeled probe-target complexes in the sample; and

20 detecting labeled probe-target complexes by illuminating with a label excitation wavelength and detecting light emission of at least one label emission wavelength.

20. A method according to Claim 19, wherein the target analyte is a polynucleotide and the probe is a biotinylated polynucleotide having a substantially complementary sequence
25 and that specifically hybridizes to the target polynucleotide under binding conditions.

21. A method according to Claim 20, wherein the up-converting label comprises an up-converting phosphor particle and
30 streptavidin.

22. A method according to Claim 19, wherein the probe is a primary antibody and the label is bound to the probe through at least one secondary antibody.

23. A method according to Claim 22, wherein said secondary antibody is biotinylated and said label is bound to streptavidin.

5 24. A method for detecting a biotinylated target, comprising the steps of:

contacting an up-converting phosphor label with streptavidin to form a streptavidin-coated up-converting phosphor label;

10 contacting said biotinylated target with said streptavidin-coated up-converting label under binding conditions to form target-label complexes;

separating target-label complexes from unbound streptavidin-coated up-converting phosphor label; and

15 detecting target-label complexes by illuminating with a label excitation wavelength and detecting light emission of at least one label emission wavelength.

25 25. A method According to Claim 24, wherein the target is a biotinylated magnetic bead.

26. A composition comprising an up-converting label and a probe.

25 27. A composition according to Claim 26, wherein the up-converting label is an up-converting inorganic phosphor.

30 28. A composition according to Claim 27, wherein the probe is selected from the group consisting of: antibodies, avidin, streptavidin, *Staphylococcus aureus* Protein A, antigens, and polynucleotides.

29. A composition according to Claim 26, wherein the probe is attached to an up-converting label by noncovalent linkage.

30. A composition according to Claim 28, wherein the probe is streptavidin and the up-converting inorganic phosphor is attached to the probe by noncovalent linkage.

5 31. A composition of Claim 30 further comprising a biotinylated magnetic bead, a streptavidin-coated magnetic bead, an avidin-coated magnetic bead, or an immunoglobulin-coated magnetic bead.

10 32. Apparatus for performing diagnostics on a sample possibly containing an up-converting luminescent reporter characterized by an excitation band in a first range of wavelengths and an emission band in a second range of wavelengths that are shorter than the wavelengths in the first range, the apparatus
15 comprising:

a source capable of emitting light in a range of wavelengths that overlaps with at least a portion of the excitation band of the reporter;

means for energizing said source;

20 a detector capable of detecting light in a range of wavelengths that overlaps with at least a portion of the emission band of the reporter;

first means for directing at least a portion of the light emitted by said source to a location at the sample,
25 including light in the first range of wavelengths and excluding light in the second range of wavelengths;

second means for directing at least a portion of the light emanating from said location at the sample to said detector, including light in the second range of wavelengths;

30 means, coupled to said detector, for generating an electrical signal representative of the intensity of light incident on said detector in a range of wavelengths that includes wavelengths in the second range and excludes wavelengths in the first range.

35

33. The apparatus of claim 32 wherein:

said detector is responsive to light in the first and second ranges; and

said second means for directing includes a wavelength-selective element; and

5 only light having wavelengths in the second range reaches said detector.

10 34. The apparatus of claim 32 wherein the excitation band is in the near infrared and the emission band is in the visible.

35. The apparatus of claim 32 wherein said first and second means for directing have no elements in common.

15 36. The apparatus of claim 32 wherein said first and second means for directing have at least one element in common.

37. The apparatus of claim 32 wherein the sample possibly further contains a second reporter characterized by an excitation band in a third range of wavelengths and an
20 emission band in a fourth range of wavelengths, and wherein the first and third ranges do not overlap and the second and fourth ranges do not overlap, and further comprising:
a second source capable of emitting light in a range of wavelengths that overlaps with at least a portion of the
25 excitation band of the second reporter;

means for energizing said second source;

a second detector capable of detecting light in a range of wavelengths that overlaps with at least a portion of the emission band of the second reporter;

30 third means for directing at least a portion of the light emitted by said second source to a location at the sample, including light in the third range of wavelengths and excluding light in the fourth range of wavelengths;

35 fourth means for directing at least a portion of the light emanating from said location at the sample to said detector, including light in the fourth range of wavelengths; and

additional means, coupled to said second detector,
for generating an electrical signal representative of the
intensity of light incident on said second detector in a range
of wavelengths that includes wavelengths in the fourth range
5 and excludes wavelengths in the first, second, and third
ranges.

38. The apparatus of claim 37 wherein:

said second and fourth means for directing together
10 include at least one wavelength-selective element;

only light having wavelengths in the second range
reaches said first-mentioned detector; and

only light having wavelengths in the fourth range
reaches said second detector.

15

39. The apparatus of claim 32 wherein the sample possibly
further contains a second reporter characterized by an
excitation band in a third range of wavelengths and an
emission band in a fourth range of wavelengths, and wherein
20 the first and third ranges overlap and the second and fourth
ranges do not overlap, and further comprising:

a second detector capable of detecting light in a
range of wavelengths that overlaps with at least a portion of
the emission band of the second reporter;

25

third means for directing at least a portion of the
light emanating from said location at the sample to said
detector, including light in the fourth range of wavelengths;
and

additional means, coupled to said second detector,
30 for generating an electrical signal representative of the
intensity of light incident on said second detector in a range
of wavelengths that includes wavelengths in the fourth range
and excludes wavelengths in the first, second, and third
ranges.

35

40. The apparatus of Claim 32, wherein said source capable of emitting light generates a confocal beam of excitation illumination.

- 5 41. Apparatus for performing diagnostics on a sample possibly containing first and second up-converting luminescent reporters, wherein the first reporter is characterized by an excitation band in a first range of wavelengths and an emission band in a second range of wavelengths that are
- 10 shorter than the wavelengths in the first range, wherein the second reporter is characterized by an excitation band in a third range of wavelengths and an emission band in a fourth range of wavelengths, and wherein the first and third ranges do not overlap and the second and fourth ranges overlap, the
- 15 apparatus comprising:
- a first source capable of emitting light in a range of wavelengths that overlaps with at least a portion of the excitation band of the first reporter;
 - a second source capable of emitting light in a range
 - 20 of wavelengths that overlaps with at least a portion of the excitation band of the second reporter;
 - means for energizing said first and second sources including means for imposing different intensity patterns on said first-mentioned and second sources;
 - 25 means for directing at least a portion of the light emitted by said first and second sources to a location at the sample, including light in the first and third ranges of wavelengths and excluding light in the second and fourth ranges of wavelengths; and
 - 30 means, coupled to said detector, for generating first and second electrical signals representative of the respective intensities of light incident on said detector at wavelengths in the second and fourth ranges and outside the first and third ranges, including means for distinguishing
 - 35 said different intensity patterns.

42. The apparatus of claim 41 wherein said means for imposing different intensity patterns comprises:

a first waveform generator coupled to said first-mentioned source so as to modulate the intensity at a first
5 frequency; and

a second waveform generator coupled to said second source so as to modulate the intensity at a second frequency that is different from said first frequency.

10 43. The apparatus of claim 42 wherein said means for distinguishing comprises:

a first frequency mixer having a first input terminal coupled to said first waveform generator and a second input terminal coupled to said detector; and

15 a second frequency mixer having a first input terminal coupled to said second waveform generator and a second input terminal coupled to said detector.

20 44. The apparatus of claim 41 wherein said means for imposing different intensity patterns comprises:

a pulse generator for energizing said first-mentioned source during a first time interval and energizing said second source in a second time interval that does not overlap said first time interval.

25

45. The apparatus of claim 44 wherein said means for distinguishing comprises:

a gated integrator coupled to said pulse generator and to said detector, operable to provide separate output
30 signals for said first and second time intervals.

46. A method for performing diagnostics on a sample containing an up-converting luminescent reporter characterized by an excitation band in a first range of wavelengths and an
35 emission band in a second range of wavelengths that are shorter than the wavelengths in the first range, the method comprising:

providing a source capable of emitting light in a range of wavelengths that is within the excitation band of the reporter;

5 providing a detector capable of detecting light in a wavelength that is within the emission band of the reporter;

directing light emitted by said source to a location at the sample;

directing light emanating from said location at the sample to the detector;

10 generating an electrical signal representative of the intensity of light in a range of wavelengths that includes wavelengths in the second range and excludes wavelengths in the first range.

15 47. The method of claim 46 wherein the excitation band is in the near infrared and the emission band is in the visible.

48. A composition comprising at least one fluorescent organic dye molecule attached to an inorganic up-converting phosphor.

20

49. A composition according to Claim 48, wherein the fluorescent organic dye molecule is selected from the group consisting of: rhodamines, cyanines, xanthenes, acridines, oxazines, porphyrins, and phthalocyanines.

25

50. A composition according to Claim 48, wherein the composition is administered to a patient for photodynamic therapy by producing photocatalytic cytotoxicity upon illumination with an excitation wavelength in the infrared, 30 near-infrared, or ultra-red portion of the spectrum.

51. A method for performing a homogeneous assay for detecting the presence of a target analyte, said method comprising the steps of:

35 attaching an up-converting label to a probe forming a labeled probe;

contacting a sample containing a target analyte with the labeled probe under binding conditions forming labeled probe-target complexes;

5 contacting labeled probe-target complexes with a contact surface wherein labeled probe-target complexes are preferentially localized to the contact surface as compared to unbound labeled probe; and

10 detecting labeled probe-target complexes on said contact surface by illuminating with a label excitation wavelength and detecting light emission of at least one label emission wavelength.

52. The method of claim 51, wherein the step of detecting is performed by illuminating with a confocal beam 15 having a focal point at the contact surface and being divergent at points other than the contact surface.

53. The method of Claim 51, wherein probe-target complexes are preferentially localized to the contact surface 20 by:

magnetic localization of magnetic beads to said contact surface, wherein said probe-target complexes are preferentially localized on the magnetic beads relative to unbound labeled probe;

25 by gravitational sedimentation of probe-target complexes from unbound labelled probe, wherein said sedimented probe-target complexes are preferentially localized on the contact surface relative to unbound labeled probe; or

30 by filtration over a contact surface wherein said probe-target complexes are preferentially localized on the contact surface relative to unbound labeled probe.

1/18




FIG. 1




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4

4/18




FIG. 5A




FIG. 5B




FIG. 5C

5/18




FIG. 6

6/18




FIG. 7A




FIG. 7B




FIG. 9




FIG. 10

9/18




FIG. 11




FIG. 12




FIG. 13




FIG. 14

11/18


PHOSPHORESCENCE FOR Na(Y_{0.8}Yb_{0.18}Er_{0.02})F₄, - 975 nm PUMP

FIG. 15




FIG. 16

12/18




FIG. 17A




FIG. 17B

13/18




FIG. 18A




FIG. 18B

14/18




FIG. 19




FIG. 20

15/18




FIG. 21

16/18





FIG. 22



COMPETITIVE HOMOGENOUS ASSAY

FIG. 23

17/18





FIG. 24

18/18



IN THE PRESENCE OF ANALYTE, THE ANTIBODY COATED PHOSPHORS WILL FORM A LARGE ENOUGH COMPLEX TO DROP TO THE BOTTOM OF THE WELL

HOMOGENEOUS IMMUNOPRECIPITATION ASSAY

FIG. 25

INTERNATIONAL SEARCH REPORT

Intern al Application No
PCT/US 93/08712A. CLASSIFICATION OF SUBJECT MATTER
IPC 5 G01N33/58 G01N21/64

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 5 G01N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO,A,87 00926 (RIJKSUNIVERSITEIT LEIDEN) 12 February 1987 cited in the application & US,A,5 043 265 (J. H. TANKE ET AL.) ---	
A	US,A,5 132 242 (S. W. CHEUNG ET AL.) 21 July 1992 cited in the application ---	
A	SCIENCE vol. 248, no. 4951, 6 April 1990 pages 73 - 76 XP000381741 W. DENK ET AL. 'TWO-PHOTON LASER SCANNING FLUORESCENCE MICROSCOPY' cited in the application ---	
	-/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

17 December 1993

Date of mailing of the international search report

14. 01 94

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+ 31-70) 340-3016

Authorized officer

Cartagena y Abella,P

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	CHEMICAL ABSTRACTS, vol. 110, no. 4, 23 January 1989, Columbus, Ohio, US; abstract no. 30750b, O. YA. MANASHIROV ET AL. 'EFFECT OF THE PURITY OF INITIAL SUBSTANCES ON LUMINESCENCE INTENSITY OF ERBIUM IN ANTI-STOKES LUMINOPHORES.' page 457 ; see abstract & VYSOKOCHIST. VESHCHISTVA vol. 3 , 1988 , RUSS. pages 198 - 201 ---	3
A	EP,A,0 476 556 (TAKEDA CHEMICAL INDUSTRIES, LTD) 25 March 1992 see the whole document ---	32-45
A	US,A,4 100 416 (T. R. HIRSCHFELD ET AL.) 11 July 1978 see the whole document ---	32-45
A	US,A,4 724 217 (S. M. MILLER) 9 February 1988 see the whole document -----	32-45

INTERNATIONAL SEARCH REPORT

Information on patent family members

Internat'l Application No

PCT/US 93/08712

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO-A-8700926	12-02-87	EP-A, B 0232357 JP-T- 63500400 US-A- 5043265	19-08-87 12-02-88 27-08-91
US-A-5043265	27-08-91	EP-A, B 0232357 JP-T- 63500400 WO-A- 8700926	19-08-87 12-02-88 12-02-87
US-A-5132242	21-07-92	US-A- 5194300	16-03-93
EP-A-0476556	25-03-92	JP-A- 5034290	09-02-93
US-A-4100416	11-07-78	NONE	
US-A-4724217	09-02-88	NONE	

17/18





FIG. 24

18/18



HOMOGENEOUS IMMUNOPRECIPITATION ASSAY

FIG. 25

INTERNATIONAL SEARCH REPORT

Intern. Application No.

PCT/US 93/08712

A. CLASSIFICATION OF SUBJECT MATTER
IPC 5 G01N33/58 G01N21/64

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 5 G01N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO,A,87 00926 (RIJKSUNIVERSITEIT LEIDEN) 12 February 1987 cited in the application & US,A,5 043 265 (J. H. TANKE ET AL.) ---	
A	US,A,5 132 242 (S. W. CHEUNG ET AL.) 21 July 1992 cited in the application ---	
A	SCIENCE vol. 248, no. 4951, 6 April 1990 pages 73 - 76 XP000381741 W. DENK ET AL. 'TWO-PHOTON LASER SCANNING FLUORESCENCE MICROSCOPY' cited in the application --- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- 'A' document defining the general state of the art which is not considered to be of particular relevance
- 'E' earlier document but published on or after the international filing date
- 'L' document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- 'O' document referring to an oral disclosure, use, exhibition or other means
- 'P' document published prior to the international filing date but later than the priority date claimed

- 'T' later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- 'X' document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- 'Y' document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- '&' document member of the same patent family

Date of the actual completion of the international search

17 December 1993

Date of mailing of the international search report

14. 01 94

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+ 31-70) 340-3016

Authorized officer

Cartagena y Abella,P

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	CHEMICAL ABSTRACTS, vol. 110, no. 4, 23 January 1989, Columbus, Ohio, US; abstract no. 30750b, O. YA. MANASHIROV ET AL. 'EFFECT OF THE PURITY OF INITIAL SUBSTANCES ON LUMINESCENCE INTENSITY OF ERBIUM IN ANTI-STOKES LUMINOPHORES.' page 457 ; see abstract & VYSOKOCHIST. VESHCHISTVA vol. 3 , 1988 , RUSS. pages 198 - 201 ----	3
A	EP,A,0 476 556 (TAKEDA CHEMICAL INDUSTRIES, LTD) 25 March 1992 see the whole document ----	32-45
A	US,A,4 100 416 (T. R. HIRSCHFELD ET AL.) 11 July 1978 see the whole document ----	32-45
A	US,A,4 724 217 (S. M. MILLER) 9 February 1988 see the whole document -----	32-45

INTERNATIONAL SEARCH REPORT

Information on patent family members

Intern 21 Application No

PCT/US 93/08712

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO-A-8700926	12-02-87	EP-A, B 0232357 JP-T- 63500400 US-A- 5043265	19-08-87 12-02-88 27-08-91
US-A-5043265	27-08-91	EP-A, B 0232357 JP-T- 63500400 WO-A- 8700926	19-08-87 12-02-88 12-02-87
US-A-5132242	21-07-92	US-A- 5194300	16-03-93
EP-A-0476556	25-03-92	JP-A- 5034290	09-02-93
US-A-4100416	11-07-78	NONE	
US-A-4724217	09-02-88	NONE	